


(SUBMIT IN TRIPLICATE)

Indian Agency NavajoUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYAllottee Chimney RockLease No. 2-140-Sub-7402

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 12, 1957Well No. 1 is located 2000 ft. from N line and 2000 ft. from W line of sec. 22SE 1/4 of 22
(1/4 Sec. and Sec. No.)7-2-E 2-17-W
(Twp.) (Range)WPM
(Meridian)WildcatSan Juan CountyNew Mexico

(Field)

(County or Subdivision)

(State or Territory)

The elevation of the ground casement above sea level is 5242 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Reynolds Mining Corporation reached a total depth of 6516 feet in an 8 3/4 inch hole on March 9, 1957. No commercial shows of oil or gas were encountered during the drilling of this well. On March 9, 1957 verbal permission was received from Mr. J. W. Long of the U. S. Geological Survey office in Farmington, New Mexico to plug and abandon this well. The well was plugged in the following manner: 25 sacks cement from 7000 to 7700 feet, 25 sacks cement from 6000 to 6700 feet, 25 sacks cement from 5000 to 5700 feet, 25 sacks cement from 4000 to 4700 feet, 25 sacks cement from 3000 to 3700 feet, 15 sacks cement from 670 to 700 feet, and 10 sacks cement in collar. All cement contained 10 percent gal. An appropriate sign and marker were placed at the well site. The location will be restored as nearly as possible to its original status and the U. S. Geological Survey office in Farmington, New Mexico will be notified of the completion date. All measurements being from belly bushing which is 11.45 feet above ground level. Well was plugged and abandoned on March 11, 1957.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Reynolds Mining Corporation
Oil and Gas Division
 Address 1524 East Ninth Street
Pack Office Box 1300
Durango, Colorado

921

By

Title

COPY Original

Signed By

C. J. [Signature]

District Petroleum Engineer

