

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well  gas well  other

2. NAME OF OPERATOR  
W.M. Gallaway

3. ADDRESS OF OPERATOR  
101-2 Petroleum Plaza Bldg. Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 660' FNL 660' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:  
TEST WATER SHUT-OFF   
FRACTURE TREAT   
SHOOT OR ACIDIZE   
REPAIR WELL   
PULL OR ALTER CASING   
MULTIPLE COMPLETE   
CHANGE ZONES   
ABANDON\*   
(other)

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

3. LEASE  
14-20-604-1893

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
UTE MOUNTAIN INDIAN

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
UTE INDIAN D

9. WELL NO.  
14

10. FIELD OR WILDCAT NAME  
VERDE GALLUP

11. SEC., T., R., M., OR BLK AND SURVEY OR AREA  
Sec. 24, T31N, R15W

12. COUNTY OR PARISH  
SAN JUAN

13. STATE  
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5589

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 5/8/81 Filled hole w/gel water, circulated hole w/45<sup>0</sup> tubing sub. Spotted 14 sks. cement across Gallup perms. 2607'-2570' and continued up 5 1/2" to 2506
- 5/9/81 Tagged cement @ 2503' Spotted 29 sks. cement across top of Point Lookout 1250'-1350'
- 6/3/81 Stretch csg. and shot @ 843' Spotted 29 sks. cement across 5 1/2" stub 893'-793'
- 6/4/81 Spotted 20 sks cement across bottom of surface 50'
- 6/6/81 Spotted 10 sks cement top of surface, erect dry hole marker, and clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Robert A. Bush* TITLE Agent

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

