

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved.  
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
W.M. Gallaway

3. ADDRESS OF OPERATOR  
101-02 Petroleum Plaza Bldg. Farmington, N.M.

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 729' FSL, 2004' FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED  
AUG 19 1981  
U. S. GEOLOGICAL SURVEY  
DURANGO, COLO.

5. LEASE  
14-20-151-46  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
UTE MOUNTAIN INDIAN  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
UTE INDIAN A  
9. WELL NO.  
9  
10. FIELD OR WILDCAT NAME  
VERDE GALLUP  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
SEC. 15, T31N, R15W  
12. COUNTY OR PARISH  
SAN JUAN  
13. STATE  
N.M.  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5807

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/23/81 Tagged fill 2285, Filled hole w/gel water circulated w/45" tubing sub. to 2305' Spotted 40 sk cement over Gallup perf. and 50' above perf.  
5/29/81 Tagged top of cement @ 2010', stretch csg. and shot 5 1/2" @ 1030' pulled csg.  
5/30/81 Spotted 15 sk cement across STUB 1055'-1005'  
Spotted 29 sk cement across Point Lookout 550'-450'  
Spotted 20 sk cement at bottom of surface  
6/6/81 Spotted 10 sk cement top of hole, set dry hole marker, clean location.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*William A. Bush*

TITLE

*Agent*

DATE

*8/14/81*

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

RECEIVED  
AUG 27 1981  
OIL CON. DIV.