

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
W.M. Gallaway
3. ADDRESS OF OPERATOR
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 729' FSL, 2004' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

RECEIVED
AUG 19 1981
U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE
14-20-151-46
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE MOUNTAIN INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
UTE INDIAN A
9. WELL NO.
9
10. FIELD OR WILDCAT NAME
VERDE GALLUP
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 15, T31N, R15W
12. COUNTY OR PARISH
SAN JUAN
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5807

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/23/81 Tagged fill 2285, Filled hole w/gel water circulated w/45⁰ tubing sub. to 2305' Spotted 40 sk cement over Gallup perf. and 50' above perf.

5/29/81 Tagged top of cement @ 2010', stretch csg. and shot 5½" @ 1030' pulled csg.

5/30/81 Spotted 15 sk cement across STUB 1055'-1005'
Spotted 29 sk cement across Point Lookout 550'-450'
Spotted 20 sk cement at bottom of surface

6/6/81 Spotted 10 sk cement top of hole, set dry hole marker, clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

David J. Miller

TITLE

Agent

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY

David J. Miller

TITLE

Agent

DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

FEB 28 1984

OIL CON. DIV.
DIST. 3