

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well ☐ other
2. NAME OF OPERATOR
W. M. Gallaway
3. ADDRESS OF OPERATOR
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FSL, 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED

AUG 19 1981

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/24/81 Tagged bottom @ 1991' Filled hole w/gel water, circulated w/45 tubing sub. Spotted 14 sk cement over Gallup perf. 1991' - 1886' and 50' above into 4½" csg.

5/6/81 Tagged top of cement 1836', shot csg.

5/7/81 Casing would not pull

5/18/81 Stretch csg. shot @ 640' pulled casing
Spotted 18 sks cement across STUB 615'-567'
Spotted 25 sks cement across top of Point Lookout 330'-230'
Spotted 18 sks cement across bottom of surface

5/28/81 Spotted 10 sk cement plug top of hole, erect dry hole marker, and clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert D. Bush TITLE *Agent*

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY

David J. Miller

TITLE

DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

FEB 28 1984

OIL CON. DIV.
DIST. 3