Form appr Budget Bu	oved. reau No. 4	2-R369.4.
ընդ²0ք ը ս	H-090 140. 5	P 2000121

Forn (Ar	n 9-3 oril 198	81 D (2)	
			

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Indian Agency
WINDOW ROCK
Allettee Navajo Tribal
Losso No. 11:-08-0001-820 11:-20-603-2022
11:-20-603-2022

		SUBSEQUENT R	PORT OF WATER SHUT-OFF		-
OTICE OF INTENTION TO DRILL	RNC	SUBSEQUENT RI	PORT OF SHOOTING OR ACIDIC	ZING	-[
OTICE OF INTENTION TO CHANGE PLA	SHIIT-OFF	SUBSEQUENT R	EPORT OF ALTERING CASING		-[
OTICE OF INTENTION TO TEST WATER OTICE OF INTENTION TO REDRILL OR	REPAIR WELL	SUBSEQUENT R	EPORT OF REDRILLING OR REP	AIR	-
		SUBSEQUENT R	EPORT OF ABANDONMENT		-1
OTICE OF INTENTION TO SHOOT OR A OTICE OF INTENTION TO PULL OR AL	TER CASING	SUPPLEMENTAR	Y WELL' HISTORY		-
OTICE OF INTENTION TO ABANDON W			o water injection	X	-
OIRE OF INTERVIOLE TO THE					=
(INDICATE	E ABOVE BY CHECK MARK N	iature of Report,	NOTICE, OR OTHER DATA)		
		M	urch 22	, 19.63	L
HORSESTIOE GALLUP	ा ल ग ण		ne i		
ell No. 80 is loca	ated 674 ft. from	m line and	1679 ft. from E	ine of sec. 14	
	•		MPIN		
A SEA SEC. IL	31N (Twp.)	(Range)	(Meridian)		3 V
(% Sec. and Sec. No.)	SAN JUAL	W.	HEM JEXIC	0 W	., U
SESHOE GAILUP		or Subdivision)	(State of	Perritory)	19
(Field)	md		r.		IS
ne elevation of the derrick	floor above sea le	vel is	It.		
TO CTO A MATORIA OF THE TANK A				三二十五 任法司	Military C
			V		
	DETAI	LS OF WOR	K	to mudding lobs, can	. KSW
rate names of and expected depths to	DETAl	LS OF WOR	K gths of proposed casings; indic sposed work)	ate mudding jobs, cen	ient-
tate names of and expected depths to	o objective sands; show siz	es, weights, and ler other important pro	gths of proposed casings; indic oposed work)	ate mudding jobs, cen	uCn .
state names of and expected depths to	o objective sands; show six ing points, and all	ces, weights, and ler other important pro	gths of proposed casings; indicaposed work)	THE PATE VALUE OF	uCn
ulled rode and tubing	o objective sands; show size ing points, and all of the perforated	ther important pro	gths of proposed casings; indies opposed work) ohlumberger - Set	ong 11:71-11:9	nc" 7 wit
ulled rode and tubing strievable bridge plu	o objective sands; show sizing points, and all o	tes, weights, and ler other important pro 1471-1497 S and water i	gths of proposed casings; indies sposed work) ichlumberger. Set recture perforati	ons 11:71-11:9	Avers
ulled rode and tubing strievable bridge plu 0,000# 10/20 aand in	o objective sands; show sizing points, and all of the points are all of the points are at 1507 . S	lights, and ler other important pro- light light 11:97 S and water is water. Pro-	gths of proposed casings; indies sposed work) ichlumberger - Set recture perforati apped into formati	ons 1471-149 on at 1000#	ncu 7 witi Avers Job
etrievable bridge plu 0,000 10/20 sand in 1te 39 BPM at 800%.	o objective sands; show size ing points, and all of the points, and	1471—1497 S and water in water. Po	gths of proposed casings; indies posed work) ichlumberger. Set racture perforati imped into formati 300% to vacuum in	ons 1471-149 on at 1000# 5 minutes. Model A Ten	ncu 7 wit Avers Job Job
etrievable bridge plu 0,000 10/20 sand in 1te 39 BPM at 800 complete 3-5-63. Class	o objective sands; show size ing points, and all of the points of the po	ice, weights, and ler other important pro- light light start and water in water. For in pressure lug and reco	gths of proposed casings; indies posed work) chlumberger. Set racture perforati imped into formati 300# to vacuum in wered. Set Baker arted injection we	ons 1471-149 on at 1000# 5 minutes. Model A Ten	ncu 7 witi Avers Job Bion
etrievable bridge plu 0,000 10/20 sand in 1te 39 BPM at 800 complete 3-5-63. Class	o objective sands; show size ing points, and all of the points of the po	ice, weights, and ler other important pro- light light start and water in water. For in pressure lug and reco	gths of proposed casings; indies posed work) chlumberger. Set racture perforati imped into formati 300# to vacuum in wered. Set Baker arted injection we	ons 1471-149 on at 1000# 5 minutes. Model A Ten	ncu 7 wit Avers Job Job
alled rode and tubing strievable bridge plu 0,000f 10/20 sand in ate 39 BPM at 800f. omplete 3-5-63. Cles acker on 2" EUE 8R hanto Lower Gallup and	o objective sands; show size ing points, and all of the points of the po	in pressure in 1520. State Upper Ge	gths of proposed casings; indies posed work) chlumberger. Set racture perforati imped into formati 300# to vacuum in wered. Set Baker arted injection we	ons 1471-149 on at 1000# 5 minutes. Model A Ten	ncu 7 witi Avers Job Bion
alled rode and tubing etrievable bridge plu 0,000f 10/20 sand in ate 39 BPM at 800f. complete 3-5-63. Clea acker on 2" EUE 8R land nto Lower Gallup and	o objective sands; show size ing points, and all of the points of the po	in pressure in 1520. State Upper Ge	gths of proposed casings; indicaposed work) chlumberger. Set recture perforati mped into formati 300# to vacuum in wered. Set Baker arted injection wa allup on 3-22-63.	ons 1471-149 on at 1000# 5 minutes. Model A Ten ster down tub	ncu 7 wit Avers Job Job
alled rode and tubing strievable bridge plus 0,000 10/20 sand in ate 39 EPM at 800%. Omplete 3-5-63. Clean acker on 2" EUE 8R banto Lower Gallup and "Effective To lining 6"	Perforated get 1507 . S 10,000 gallons Initial shut i aned sand to pl .7# J-55 tbg at armulus into t company changed	li71-li97 S and water in water. Po n pressure ug and rece 1520. Ste che Upper Ge tts name to	gths of proposed casings; indicaposed work) chlumberger. Set recture perforati mped into formati 300# to vacuum in wered. Set Baker arted injection wa allup on 3-22-63.	ons 1471-149 on at 1000# 5 minutes. Model A Ten ster down tub	ncu 7 wit Avers Job Job
alled rode and tubing strievable bridge plu 0,000f 10/20 sand in ate 39 BPM at 800f. complete 3-5-63. Clean acker on 2" EUE 8R b. nto Lower Gallup and	Perforated get 1507 . S 10,000 gallons Initial shut i aned sand to pl .7# J-55 tbg at armulus into t company changed	li71-li97 S and water in water. Po n pressure ug and rece 1520. Ste che Upper Ge tts name to	gths of proposed casings; indisposed work) chlumberger. Set racture perforation and into formation and into the second into the second into the second injection was allup on 3-22-63.	ons 11:71-11:9 on at 1000# 5 minutes. Model A Ten ter down tub	ncr 7 witi Avers Job Mion
alled rode and tubing strievable bridge plu 0,000f 10/20 sand in ate 39 BPM at 800f. complete 3-5-63. Clean acker on 2" EUE 8R b. nto Lower Gallup and	o objective sands; show size ing points, and all of the points in the points and all of the points are point	li71-li97 S and water in water. Po n pressure ug and rece 1520. Ste che Upper Ge tts name to	gths of proposed casings; indisposed work) chlumberger. Set racture perforation and into formation and into the second into the second into the second injection was allup on 3-22-63.	ons 11:71-11:9 on at 1000# 5 minutes. Model A Ten ter down tub	ncu 7 witi Avers Job Bion
alled rode and tubing etrievable bridge plu 0,000# 10/20 sand in ate 39 HPM at 800#. omplete 3-5-63. Clea acker on 2" EUE 8R hanto Lower Gallup and "Effective "Atlantic R	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chichfield Company	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Model A Ten ter down tub [EIVED] R 2 7 1963	ncr 7 witi Avers Job Mion
alled rode and tubing strievable bridge plu 0,000 10/20 sand in ate 39 BPM at 800%. omplete 3-5-63. Clea acker on 2" EUE 6R h. nto Lower Gallup and "Effective "Atlantic B	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chaffield Company changed company changed	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Nodel A Tenter down tub [EIVED] R 2 7 1963	ncu 7 witi Avers Job sion
etrievable bridge plu 0,000 10/20 sand in ate 39 EPM at 800%. complete 3-5-63. Clean acker on 2" EUE 6R land "Effective radining of Atlantic B	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chaffield Company changed company changed	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Model A Ten ter down tub [EIVED] R 2 7 1963	ncu 7 wit Avers Job Job
alled rode and tubing strievable bridge plus 0,000 10/20 sand in ate 39 BPM at 800%. Omplete 3-5-63. Clear control lower Gallup and "Effective Tables of Wellantic E	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chaffield Company changed company changed	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Nodel A Tenter down tub [EIVED] R 2 7 1963	ncu 7 witi Avers Job sion
etrievable bridge plu 0,000 10/20 sand in ate 39 HPM at 800 complete 3-5-63. Clea acker on 2" EUE 8R h. nto Lower Gallup and "Effective Atlantic B	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chaffield Company changed company changed	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Nodel A Tenter down tub [EIVED] R 2 7 1963	ncu 7 witi Avers Job sion
alled rode and tubing etrievable bridge plu 0,000 10/20 sand in ate 39 BPM at 800%. complete 3-5-63. Clea acker on 2" EUE 8R in nto Lower Gallup and "Effective "Atlantic R I understand that this plan of we Company The Atlanti	Perforated g at 1507 S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed chaffield Company changed company changed	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Nodel A Tenter down tub [EIVED] R 2 7 1963	ncr 7 witi Avers Job Mion
etrievable bridge plu 0,000 10/20 and in ate 39 BPM at 800%. omplete 3-5-63. Clea acker on 2" EUE 8R ha nto Lower Gallup and "Effective "Atlantic B	Perforated g at 1507. S 10,000 gallons Initial shut i aned sand to pl 77 J-55 tbg at armulus into t company changed Sichfield Company Company changed Sichfield Company Company Changed Co	li71-li97 S and water in n pressure lug and rece lug and	gths of proposed casings; indicaposed work) chlumberger. Set racture perforation and into formation and into the set of	ons 11:71-11:9 on at 1000# 5 minutes. Nodel A Tenter down tub [EIVED] R 2 7 1963	ncu 7 witi Avers Job sion