

District I  
P.O. Box 1980, Hobbs, NM  
District II  
P.O. Drawer DD, Artesia, NM 88211  
District III  
1000 Rio Brazos Rd, Aztec, NM 87410

State of New Mexico  
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

SUBMIT 1 COPY TO  
APPROPRIATE  
DISTRICT OFFICE  
AND 1 COPY TO  
SANTA FE OFFICE

*Denny G. Fount*  
*Approved*  
*2/19/97*  
**PIT REMEDIATION AND CLOSURE REPORT**

Operator: Snyder Oil Corporation Telephone: 505/632-8056  
Address: Post Office Box 2038, Farmington, NM 87499-2038  
Facility Or: Jackson #2E  
Well Name \_\_\_\_\_  
Location: Unit or Qtr/Qtr Sec 0 Sec 18 T 31N R 12W County San Juan  
Pit Type: Separator x Dehydrator \_\_\_\_\_ Other \_\_\_\_\_  
Land Type: BLM x, State \_\_\_\_\_, Fee \_\_\_\_\_, Other \_\_\_\_\_


Pit Location: Pit dimensions: length 10', width 10', depth 3'  
(Attach diagram) Reference: wellhead x, other \_\_\_\_\_  
Footage from reference: 60'  
Direction from reference: S Degrees 10° East North \_\_\_\_\_  
of \_\_\_\_\_ West South \_\_\_\_\_

Depth To Ground Water: Less than 50 feet (20 points)  
(Vertical distance from 50 feet to 99 feet (10 points)  
contaminants to seasonal Greater than 100 feet (0 Points) 0  
high water elevation of ground water)

Wellhead Protection Area: Yes (20 points)  
(Less than 200 feet from a private No (0 points) 0  
domestic water source, or; less than  
1000 feet from all other water sources)

Distance To Surface Water: Less than 200 feet (20 points)  
(Horizontal distance to perennial 200 feet to 1000 feet (10 points)  
lakes, ponds, rivers, streams, creeks, Greater than 1000 feet (0 points) 0  
irrigation canals and ditches)

RANKING SCORE (TOTAL POINTS): 0



Date Remediation Started: 6/10/94 Dated Completed: 6/10/94

Remediation Method: Excavation X Approx. cubic yards 50  
(Check all appropriate sections)

Landfarmed      Insitu Bioremediation     

Other Pit contents removed, stirred and returned to excavation

Remediation Location: Onsite X Offsite       
(ie. landfarmed onsite, name and location of offsite facility)

General Description Of Remedial Action: Excavated soils were stockpiled on the surface and sampled with a PID meter. There were no signs of significant contamination as the field headspace readings were all less than 30 ppm. The excavated material was returned to the pit and stirred with a backhoe. After mixing thoroughly, a composite fill material bottom sample was taken. See below and the attached lab report.

Ground Water Encountered: No X Yes      Depth     

**Final Pit:**

**Closure Sampling:**  
(if multiple samples, attach sample results and diagram of sample locations and depths)

Sample location Pit bottom center

Sample depth 10 ft

Sample date 6/10/94

Sample time 2:13 pm

**Sample Results**

Benzene(ppm) n/a

Total BTEX(ppm) n/a

Field headspace(ppm) 26 ppm

TPH 135 ppm

Ground Water Sample: Yes      No X (If yes, attach sample results)


I HEREBY CERTIFY THAT THE INFORMATION ABOVE IS TRUE AND COMPLETE TO THE BEST OF MY KNOWLEDGE AND BELIEF

DATE Oct. 22, 1996

SIGNATURE Shawn Adams

PRINTED NAME Shawn Adams, Env Consultant  
AND TITLE Contract Env. Services, Inc.

Pit Excavation Soil Log			
Wellname	Jackson 2E		
Depth (ft)	Description		
0	Silty clay and sand		
1	"		
2	"		
3	"		
4	"		
5	"		
6	Moist clay		
7	"		
8	"		
9	"		
10	"	PID meter:	26 ppm



○  
wellhead

