

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Santa FeLease No. 078707

Unit _____

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 20, 1962

Duke
Well No. 1-13 is located 1850 ft. from N line and 1190 ft. from E line of sec. 13


NE/4 Sec. 13 31N 13W NMPM
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Basin Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

Blanco Mesaverde
The elevation of the derrick floor above sea level is 5815 ft. Ground
5827 KB

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 8-3/4" hole to 6810' - ran 209 joints 5-1/2" 15.5# J-55 casing - set @ 6807 KB. Cemented thru shoe with 111 sx regular and 111 sx Diamix "A". Bumped plug with 2000 psi - plug down @ 2:20 A.M. 11-24-62. Cemented thru stage collar @ 4780' - with 218 Pt³ 40% Diacel D, 37 sx reg. cement and 37 sx Diamix A. Plug down @ 6 A.M. 11-25-62, bumped plug with 2000 psi - held OK.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Consolidated Oil & Gas, Inc.Address 4150 East MexicoDenver 22, ColoradoBy W. WilliamsTitle Chief Engineer

