## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

## MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

OIL CON. COM. DIST. 3

Poc	ol Bas	in	-	F	ormation	n Dak	ota	··-	County_	San Jus	an	
Initial X Annual												
Company Adobe O11												
Unit G Sec. 14 Twp. 31N Rge. 13W Purchaser												
Casing 4-1/2 Wt. 10.5 I.D. Set at 6746 Perf. 6546 To 6660												
Tubing 2-3/8 Wt. 4.7 I.D. Set at 6634 Perf. Open-ended To												
Gas Pay: From 6546 To 6660 L xG 65 -GL Bar. Press.												
Producing Thru: Casing Tubing X Type Well Single Gas												
Date of Completion: 4-8-62 Packer Reservoir Temp.												
OBSERVED DATA												
Tested Through (Prover) (Choke) (Meter) Type Taps												
<u> </u>	Flow Data			ata	Tubj			ng Data   Casing Data			<del></del>	
No.	(Prover (Line)	·)   (C	hoke)	Press.	Diff.	J .	Press	Temp.	Press.	Temp.	Duration of Flow	
SI	Size			psig	h <sub>w</sub>	°F.	psig	°F.	psig	°F.	Hr.	
$\frac{S1}{1.}$		+					1840	<del></del>	1846			
2.			3/4"	107					394	73	3 hrs.	
3. 4.												
5.								<del></del>		ļ		
						7.01.047	~	<del></del>		<u> </u>	<b>L</b>	
T	Coeffi	cient	1	Pr	FLOW CALCULATIONS				Gravity Compress. Rate of Flow			
No.	(24-Hour)		√ h <sub>w</sub> I	$\sqrt{h_{\mathbf{w}}p_{\mathbf{f}}}$ r		Factor F <sub>t</sub>		Factor Fg	Factor Q-MCFPD			
1. 2.									F			
$\frac{2}{3}$ .	12.365			119		9877		06.00	1.011		1/10	
3. 4. 5.						<u> </u>		9608_	1.00.		1412	
2.1					PRI	ESSURE CA	A COUT A TOTA	ONG				
as I	Liquid H <del>yd</del> ı	rocarbo	on Ratio	)			_		fic Gravit	tu Sann	unatom Coo	
as Liquid Hydrocarbon Ratiocf/bbl. Specific Gravity Separator Gas ravity of Liquid Hydrocarbonsdeg. Specific Gravity Flowing Fluid												
c		<del></del>	(1	-e <sup>-8</sup> )				Pc	1858	Pg 34	52.164	
	ъ	<del></del>								<b></b>		
No.	$P_{\mathbf{w}}$	] 1	$\mathbf{P_t^2} \mid \mathbf{F_c}$	Q	$(F_cQ)^2$	(F.	(a) <sup>2</sup>	P <sub>w</sub> 2	$P_c^2 - P_w^2$	Ca	1. P	
$\leftarrow$	Pt (psia)	)				(1-	Q) <sup>2</sup> e <sup>-s</sup> )	- W	-C -W		$\frac{P_{w}}{P_{c}}$	
1. 2.		+	_									
3.	406						1	.64.836	3287.328		1,0501	
5.		<del> </del>				<del>-                                    </del>						
	lute Poter		1465			MCPPD;	n_•75	1.0373		<u>L</u>		
COMPANY Adobe Oil Co. ADDRESS 1223 Petroleum Life Bldg., Midland, Texas												
AGEN	T and TITI	E				Engineer		Original s	igned by T	. <b>A.</b> Ես	gah	
	ESSED PANY											
J. OPIL.						REMA	RKS		<del></del>	ATI		
						· - <del></del>	-		10	11176	Vin	
									/ r	FULL	Y : . U	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (P<sub>w</sub>). MCF/da. @ 15.025 psia and 60° F.
- Pc 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fnv Supercompressability factor.
- n \_ Slope of back pressure curve.

Note: If  $P_{\rm W}$  cannot be taken because of manner of completion or condition of well, then  $P_{\rm W}$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{\rm t}$ .