

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

OCT 21 1985

BUREAU OF LAND MANAGEMENT
FARMINGTON RESOURCE AREA

5. LEASE DESIGNATION AND SERIAL NO.

SF-078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Newberry

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Basin Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T31N R12W

12. COUNTY OR PARISH 13. STATE

San Juan

NM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

6046' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Set bridge plug-Dakota D Zone

(Other)

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/14/85 MIRUSU. Kill well w/1% KCL wtr. NDWH. NUBOP. RIH w/tbg and tag fill at 7152' KB. Rig up Gearhart. RIH w/Model "S" cast iron bridge plug. Hit obstruction at 7091' KB. POOH w/cast iron bridge plug and setting tool Cast iron bridge plug was scratched on btm. RIH w/bit and scraper to 6970'.

10/15/85 RIH w/bit & scraper. Tag btm at 7080'. Worked back to 7075' w/power swivel. Worked bit & scraper to 7077'. RIH w/cast iron bridge plug. (Baker Model "S") and set at 7091' KB. Rigged down Gearhart. RIH w/2-3/8" tbg and SN w/1 jt off btm and landed at 7062' KB. NDBOP. NUWH.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Senior Regulatory Analyst

DATE

10/14/85

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

OCT 23 1985

CONDITIONS OF APPROVAL, IF ANY:

FARMINGTON RESOURCE AREA

BY

sm

*See Instructions on Reverse Side

NMOCC