1	Form (Ap	9 -3 ; ril 195	81 b 2)	
	1	ŀ	ļ	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dudgov = =
Indian Agency Gallup Mavajo - Uta Mtn Tribal
Allettee
Lease No.

		T REPORT OF WATER SHUT-OFF
OTICE OF INTENTION TO DRILL		T REPORT OF WALER SHOTTEN OF ACIDIZING
OTICE OF INTENTION TO CHANGE PLAN	NSSUBSEQUEN	IT REPORT OF ALTERING CASING
THE OF INTENTION TO TEST WATER	SHU1-OFF	NT REPORT OF REDRILLING OR REPAIR
OTICE OF INTENTION TO REDRILL OR	REPAIR WELL SUBSEQUE	NT REPORT OF ABANDONMENT
OTICE OF INTENTION TO SHOOT OR AC	CIDIZE	
IOTICE OF INTENTION TO PULL OR ALT	TER CASINGSUPPLEME	NTARY WELL HISTORYUL 23 1963
TO ABANDON W	ELL	
HOTICE OF INTENTION TO ASSIST		S GEOLOGICAL SURVEY
(INDICATE	ABOVE BY CHECK MARK NATURE OF REP	FARMINGTON, NEW MEXICO
Nevajo Vell No. <u>17-2</u> is loca	ated 990° ft. from Ni line	and hoo ft. from W line of sec. 17
	31M TON_	(Meridian)
14 Sec. 17 (4 Sec. and Sec. No.)	(Twp.) (Range)	Men Merrico
	Sen Juan	(State or Territory)
Undesignated (Field)	(County or Subdivision)	(2.2.4
	floor above sea level is55 DETAILS OF W objective sands; show sizes, weights, au ing points, and all other importa-	ORK nd lengths of proposed casings; indicate mudding jobs, cement—
(State names of and expected depths to	DETAILS OF Wood of the state of	ORK and lengths of proposed casings; indicate mudding jobs, cement- nt proposed work) All Fractured with 16,000# 10/20 sand use crude. FEDP 3000/1500. Avg idge plug at 1490*.
(State names of and expected depths to the Parket of 1608 = 1613	DETAILS OF We objective sands; show sizes, weights, and all other importations of the sand	ork and lengths of proposed casings; indicate mudding jobs, cementary proposed work) HI Fractured with 16,000 10/20 sand case crude. FEDP 3000/1500. Avg. idge plug at 1490. HI 14,000 10/20 Sand and 2000 12-20 P 3500/3100 Avg. rate 25 parest 2000 ps. RELEVED JUL 2 4 1963 OU. CON. COM.
(State names of and expected depths to the Parket of 1608 = 1613	DETAILS OF Woodpective sands; show sizes, weights, are ing points, and all other importance of the sand of the san	ork and lengths of proposed casings; indicate mudding jobs, cementary proposed work) HI Fractured with 16,000# 10/20 sand case crude. FEP 3000/1500. Avg idge plug at 11:90*. HI 11:000# 10/20 Sand and 2000# 12-20 P 3500/3100 Avg. rate 25 pp. at 2000 ps.
(State names of and expected depths to the Cornected 1608 = 1613	DETAILS OF Wood objective sands; show sizes, weights, and all other importations of the sand of the sa	ork and lengths of proposed casings; indicate mudding jobs, cementary proposed work) HI Fractured with 16,000 10/20 sand case crude. FEDP 3000/1500. Avg. idge plug at 1490. HI 14,000 10/20 Sand and 2000 12-20 P 3500/3100 Avg. rate 25 parest 2000 ps. RELEVED JUL 2 4 1963 OU. CON. COM.

en de la companya de

The second secon