DEPAI	UNITED STATES RTMENT OF THE INTERI GEOLOGICAL SURVEY	OR (Other instructions of verse side)	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)			6. IF INDIAN, ALLOTTEE OR TRIBE NAME Ute Hountain Tribal
OIL GAS OTHER			7. UNIT AGREEMENT NAME
NAM DOPULATE PARTY.		8. FAIT DE LEASE NAME	
ADDRESS Co. Jazrol 064 Farmington, New Mexico		9. was no.	
LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface			10. Tarder and lapvildcat
	Section 11, 31H 15W W.	N.P.X	11S SCULLE CLERKY AND
. PERMIT NO.	15. BLEVATIONS (CRO) whether DF	, RT, GR, etc.)	12. Samu nansisi 13 curkeri
	Appropriate Box To Indicate N		그 그 이 사람들은 사람들이 살아 보고 있다면 하는데 함께 되었다.
NOTICE OF I	NTENTION TO: PULL OR ALTER CASING	WATER SHUT-OFF	BSEQUENT REPORT OF:
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING IN TENTAL	on to Abandon Ment. X
REPAIR WELL	CHANGE PLANS	(Other)	
(Other)		(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	
It is intended to plus acros L. Cement plus acros 2. Cut 7" D casing	ng and abandon this wells pay section (-18008 to at approx 1100; and put	l in the following 19121) /780 100' sement plus	S Manner: KB To FD across top (1050' 1/50')
It is intended to plus across L. Cement plus across L. Cut 7" 6D casing Coment across L./60° cement across	s pay section (18008 t at approx 1100; and put s Point-Lockout 6 178; botton of surface 120	l in the following 19121) /780 100' cement plug to 2781 //ANCOS	KB TO TD
It is intended to plus acros L. Cement plus acros 2. Cut 7" D casing 3. 100° cement acros	s pay section (18008 to at approx 1100; and put s Point-Lockout 6 178; betten of surface 120 with 10 sacks	l in the following 19121) /780 100' cement plug to 2781 //ANCOS	KB TO TD across top (1050'=1150')
It is intended to plus across. Cement plus across. Cut 7" D casing across. 100' cement across. 100' cement across. Marker installed across. FLUID BET	s pay section (18008 to at approx 1100; and put s Point-Lockout 6 178; betten of surface 120 with 10 sacks	l in the following 19121) 1780 100' cement plug to 2781 Hancos	manner: Topo de la production de la prod
It is intended to plus across. Cent 7" OD casing . 3. 100' cement across. 4./60' cement across. Marker installed of FLUID BET.	s pay section (18008 to at approx 1100; and put section of surface 120 with 10 sacks WEEN PLUGS	l in the following 19121) 1780 100' cement plug to 2781 Hancos	manner: Tory (1050) Lanner: Lanne
It is intended to plus across. Cent 7" OD casing . 3. 100' cement across. 4./60' cement across. Marker installed of FLUID BET.	s pay section (18008 to at approx 1100; and put section of surface 120 with 10 sacks WEEN PLUGS	l in the following 19121) 1780 100' cement plug to 2781 Hancos	manner (1050 / 1050 michal) Manner (1050 michal) Manne
It is intended to plus across. Cent 7" OD casing to 100' cement across. 100' cement across. Marker installed to FLUID BET	s pay section (18008 to at approx 1100; and put section of surface 120 with 10 sacks WEEN PLUGS	l in the following 19121) 1780 100' cement plug to 2781 Hancos	manner: Topo and the manner of the second and the s
It is intended to plus acros L. Cement plus acros L. Cut 7" OD casing L. 100' cement across L. 60' cement	s pay section (18008 to at approx 1100; and put section of surface 120 with 10 sacks WEEN PLUGS	l in the following 19121) 1780 100' cement plug to 2781 Hancos	Banner: 1000 How Sold at School and School and Sold at School and School
It is intended to plus acros L. Cement plus acros L. Cut 7" OD casing L. 100' cement across L. 60' cement across L. Marker installed FLUID BET	s pay section (18008 to at approx 1100; and put s Point-Lockout & 178; botton of surface 120 with 10 sacks WEEN PLUGS this work on or before 1	l in the following 19121) 1780 100' cement plug to 2781 Hancos	Ranner: 1000 (100 michal) And the Constant of
It is intended to plus acros L. Cement plus acros Cut 7" OD casing 100' cement across 1./60' cement across Marker installed FLUID BET Fould like to Start	s pay section (18008 to at approx 1100; and put s Point-Lockout & 178; botton of surface 120 with 10 sacks WEEN PLUGS this work on or before 1	l in the following 19121) 1780 100' cement plug to 2781 Hancos	Banner: 1000 (100 michae) To real table (100 michae) To
L. Cement plug acros C. Cut 7" OD casing 100' cement across 100	s pay section (18008 to at approx 1100; and put s Point Lookout 6 178; botton of surface 120 with 15 sacks WEEN PLUGS this work on or before 1	l in the following 19121) 1780 100' cement plug to 278' MANCOS Peb. 24,1965	manner: 1000 Hours and all sections of the section
It is intended to pl L. Cement plug acros 2. Cut ?" OD casing 3. 100' cement across 4./60' cement across 5. Marker installed FLUID BET fould like to Start signed	s pay section (18008 to at approx 1100; and put s Point Lockout 6 178; botton of surface 120 with 15 sacks WEEN PLUCS this work on or before 1	l in the following 19121) 1780 100' cement plug to 2781 MANCOS	manner: 1000 to service of the control of the contr
It is intended to pl L. Cement plug acros 2. Cut ?" OD casing 3. 100° cement across 4./60° cement across 5. Marker installed FLUID BET fould like to Start I hereby being this inforced SIGNED This space to Federal E. D.	s pay section (18008 to at approx 1100; and put s Point Lookout 6 178; botton of surface 120 with 10 sacks WEEN PLUGS this work on or before 1 ofice use)	l in the following 19121) 1780 100' cement plug to 278' MANCOS Peb. 24,1965	manner: To be a find the first of the first
It is intended to pl L. Cement plug acros 2. Cut ?" OD casing 3. 100' cement across 4./60' cement across 5. Marker installed FLUID BET fould like to Start signed	s pay section (18008 to at approx 1100; and put s Point Lookout 6 178; botton of surface 120 with 10 sacks WEEN PLUGS this work on or before 1 ofice use)	l in the following 19121) 1780 100' cement plug to 278' MANCOS Peb. 24,1965	To complicate the production of the control of the