

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
W.M. Gallaway
3. ADDRESS OF OPERATOR
101-02 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 919' FSL 1268' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

AUG 19 1981

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE
14-20-151-45
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
UTE INDIAN
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
VERDE GALLUP
11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T31N, R15W
12. COUNTY OR PARISH
SAN JUAN
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5697 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/28/81 Filled hole w/gel water, circulated w/45' tubing sub spotted 12 sks. cement across Gallup perfs. 1883' to 1845' and continue up to 1805' in 5 1/2" csq.

5/14/81 Tagged cement 1800', stretch csq. and shot @ 1208' pulled casing.

5/15/81 Spotted 17 sks. cement across stub 1233' to 1183'
Spotted 30 sks. cement across top of Point Lookout 550' to 450'

5/16/81 Spotted 20 sks. cement bottom of surface csq. 50'

5/28/81 Spotted 10 sks. cement in top of hole, and erect dry marker and clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Richard D. Bush TITLE *Agent*

DATE

8/14/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

