STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

er Petrol	eun	Lease _	Vickels		Well /	
s. 11 1						
ocation f Well: Unit Sec Twp 3 N NAME OF RESERVOIR OR POOL			Rge. <u>Ι</u> 3ω		County ST	
			100. e)	METHOD OF PROD. (Flow or Art LIFE)	PROD, MEDIUM (The. or Cog.)	
Upper MV			Gas +		16	
		Ga			176	
and de			Si press paid	Sta	bilized? (Yes or Na)	
	2 da	yp !	SI press. polg	Sta	bilized? (Yee or Ma)	
10.11-93	1 200	0				
## 1:00 a	10-13-93	FLOW ILDI	Zees producing	Suppor or Lower's Lore	ver	
LAPSED TIME SINCE®		URE Lewer Completion	PROD. ZONE TEMP.		REMARKS	
2 days	150	300				
					GEIVEN	
					2 3 1994 W	
uring test			<u> </u>	D_0	M. 3 DIN	
ВОР	D based on	Bbls. in	Ho	us Gra	v GOR	
hul-in	MID-TE		SI press paig	:A	ibilized? (Yes or Mo)	
			4			
	Johnson BOP	PRE-FLO Not-in Langth of time shut- 10-11-9	PRE-FLOW SHUT-IN PR D- -9	PRE-FLOW SHUT-IN PRESSURE DATE Complete Complete St press. paig	PRE-FLOW SHUT-IN PRESSURE DATA North Langth of Birms shut-in St prees. palg Sta	

FLOW TEST NO. 2

emmenced of flow, de	te) # #			Zone producing (Upper o	r Lowert	
-	LAPSED TIME	PRESSURE		PROG. 20ME	REMARKS	
	SINCE **	Upper Completion	Lower Completion	TEMP.		
· · · · - · ; - · - · ·	- ·		4			
			1	•		
	ļ	<u> </u>	ļ		and the second property of the second of the	
1			1			
			 			
	L	L	<u> </u>	<u> </u>		
oduction rate di	uring test					
L.	202	.	mi i	•	C- 007	
:	BOP	D pased on	Bbis. in	1 Hours	Grav GOR _	
:		мсғ	PD: Tested thru	(Orifice or Meter): _		
				(
marks:						
			·			
ereby certify tha	at the information	on berein contain	ed is true and co	mplete to the best of	my knowledge.	
. 1	: (\$1 'O' 72 ft	00A	_	T. Ila	Patrolan	
		994	19 C	perator <u>Fully</u>	- Petroleum	
New Mexico Oil	•	•	я	· (Xellena	Hanhardt	
0 K	les Sho		-	7 1	······································	
			T	ide agent		
DEPUTY	OH & GAS INSP	ector, dist. #3	-	1/-17-9	'3	
			D	Take $11-10-9$		

NORTHWEST NEW MEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced as each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fineture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any cime that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the sest is to be commenced. Offset operators shall also be so notified.
- 3. The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shart-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to the lack of a pipeline connection the flow period shall be three hours.
- Following completion of Flow Test No. 1, the well shall again be abut-in, in accordance with Paragraph 3 above.
- 6. Flow Test'No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the name as for Flow Test No. 1 except

- that the previously produced some shall remain shot-in while the some which was previously shor-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow-period, at fifueen-minuse intervals during the first hour thereof, and ot hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be mintinuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil sone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described sess shall be filed in triplicate within 15 days after completion of the text. Tests shall be filed with the Astec District Office of the New Mexico Oil Conservation District on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing comperatures (gas somes only) and gravity and GOR (oil somes only).