

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088

Santa Fe, New Mexico 87504-2088

DEC 26 1990

OIL CON. DIV.
DIST. 3

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.
2689-30

7. Lease Name or Unit Agreement Name

Segal 1-10

8. Well No.

1

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☐

GAS
WELL ☒

OTHER

2. Name of Operator

Benson-Montin-Greer Drilling Corp.

3. Address of Operator

221 Petroleum Center Bldg. Farmington, NM 87401

4. Well Location

Unit Letter K : 1844 Feet From The South Line and 1850 Feet From The West Line

Section 10

Township 31N

Range 13W

NMPM San Juan

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

6728' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cement plug 100 sacks below packer set at 4100' - Top inside 5 1/2" at 4172'
Perforated at 2030' - Cement plug 150 sacks - circulated through perfs
Cement plug 152 sacks inside 5 1/2" casing - Top of cement 1711'
Shot off 5 1/2" at 592' - Cement plug 30 sacks down 5 1/2" after pulling 15' 5 1/2"
POH with 14 joints 5 1/2" casing
RIH with 2 3/8" EUE tubing to 251' - Cement plug from 251' to surface
Erected dry hole marker and cemented inside surface pipe.

Above plugging procedure approved and witnessed by Charles Gholson, Deputy
Oil and Gas Inspector and/or Jeff A. Edmister, Geologist II representing New
Mexico Oil Conservation Division.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Vice President

DATE 12/21/89

(505)

TYPE OR PRINT NAME Virgil L. Stoabs

TELEPHONE NO. 325-8874

(This space for State Use)

APPROVED BY

TITLE

DEPUTY OIL & GAS INSPECTOR, DIST. #3

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 26 1990