


(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Indian Agency Navajo
Allottee 24-20-400-0004
Lease No. 24-20-400-0004
Co. Loc. No. 24-20-400-0004



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input type="checkbox"/>
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR	<input type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<u>Supplementary Report of Perforating and Fracture Treatment</u>	<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farmington, New Mexico May 8, 1959


Well No. 10 is located 200 ft. from N line and 300 ft. from E line of sec. 9
SW 1/4 of SW 1/4 Sec. 9 T-21-S R-17-W 100N
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Chimney Rock Oilfield San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3197 ft. Gr.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 4/1/59. Set 7" casing at 40'. (9" hole). Drilled plug at 9:00 A.M., 4/20/59. Drilled w/c to 875' & mudded up. Cased from 875' to 925'. Drilled to 20' of 925'. Set 4" casing at 925'. Run Gamma Ray & Collar logs. Perforated from 925' to 977' w/2 jet shots per foot. Set pumping unit. Failed to produce allowable on pumping tests. Sand/oil free w/6000 gals. lower grade and 9000' sand. Set 2" tubing at 977'. No-run rods & pump. On final 24 hour test (May 4, 1959) on 12-30" 875' pumped 21 bbls. new oil. Gov. Cr. 37.2. 625 70.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced

Company Mobile Oil & Refining Company
Address Box 1816
Farmington, New Mexico

By Russell H. Lilly
Title District Superintendent