For (I	m 9- eb. 19	331 a 951)	•	
	••••			

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office	Santa Fe
Lease No.	078146
Unit	Meuberry

NOTICE OF INTENTION TO DRILL.		SUBSEQUEN	T REPORT OF WATER SHU	JT-OFF
NOTICE OF INTENTION TO CHANGE	PLANS	SUBSEQUEN	T REPORT OF SHOOTING	OR ACIDIZING
NOTICE OF INTENTION TO TEST WA	ATER SHUT-OFF	SUBSEQUEN	T REPORT OF ALTERING	CASING
NOTICE OF INTENTION TO RE-DRIL	L OR REPAIR WELL	SUBSEQUEN	T REPORT OF RE-DRILLIN	IG OR REPAIR
NOTICE OF INTENTION TO SHOOT	OR ACIDIZE	SUBSEQUEN	T REPORT OF ABANDONM	ENT
NOTICE OF INTENTION TO PULL OF	R ALTER CASING	1 11		
NOTICE OF INTENTION TO ABANDO	N WELL	"B TEX	' Fracture	
(INDI	CATE ABOVE BY CHECK MA	ARK NATURE OF REPOR	RT, NOTICE, OR OTHER DAT	та)
			Februa	ry 15, , , , (
writh: 3 · 1	. I none	(N) ,.	I make to t	(E)
Well No. 3 is loc	ated From It. Iro	line an	d Far it. from	line of sec. C
NE section 5	31N	12%	MPH	·~•
(1/2 Sec. and Sec. No.)	(Twp.)	(Range)	(Meridian)	
(Field)	(Count	ty or Subdivision)	(St	ate or Territory)
	DET.	AILS OF WO	RK ngths of proposed casing:	s; indicate mudding jobs, ce
The elevation of the derrice State names of and expected depths February 13, 1956 Thater fractured upper 4766' - 4778', 4794' gallons water and 95 1000#, average treat 2100 gallons.	DET. to objective sands; show ing points, and al biel mepth 507; r Point Lockou - 4000', and i ,000; sand. In	AILS OF WOI sizes, weights, and le ill other important properties to perforate \$602' - \$608 reakdown pre-	RK ngths of proposed casing opposed work) ry bridge plug d intervals 47 ' (4 holes/ft.	at 4050'. 54' - 4760',) with 100,400
State names of and expected depths February 13, 1956 T kater fractured upper 4766' - 4778', 4794' gallons water and 95 1000#, average treat	DET. to objective sands; show ing points, and al biel mepth 507; r Point Lockou - 4000', and i ,000; sand. In	AILS OF WOI sizes, weights, and le ill other important properties to perforate \$602' - \$608 reakdown pre-	RK ngths of proposed casing opposed work) ry bridge plug d intervals 47 ' (4 holes/ft. seure 700, mail on rate 64 bb.	at 4050'. 54' - 4760',) with 100,400
February 13, 1956 Twater fractured upper 4766; 4794; gellons water and 95 1000#, average treat 6100 gellons.	DETA to objective sands; show ing points, and al coal septh 507; r Point Lookou - 4000', and a ,000# sand. In ing pressure 7;	AILS OF WOI sizes, weights, and led to ther important property. Perspore to perforate \$602' - 4508 reakdown presport. Inject	ngths of proposed casing opposed work) ry bridge plug d intervals 47 ' (4 holes/ft. seure 700, mail ion rate 64 bb.	at 4050'. 54' - 4760',) with 100,400 ximum pressure ls /min. Flush
State names of and expected depths February 13, 1956 The star fractured upper 4766' - 4778', 4794' gallons water and 95 1000#, average treat 2100 gallons.	DETA to objective sands; show ing points, and al coal septh 507; r Point Lookou - 4000', and a ,000# sand. In ing pressure 7;	AILS OF WOI sizes, weights, and led to ther important property. Perspore to perforate \$602' - 4508 reakdown presport. Inject	ngths of proposed casing opposed work) ry bridge plug d intervals 47 ' (4 holes/ft. seure 700, mail ion rate 64 bb.	at 4050'. 54' - 4760',) with 100,400 ximus pressure 1s /sin. Flush 141956 CON. COM.
February 13, 1956 Twater fractured upper 4766; 4794; gellons water and 95 1000#, average treat 6100 gellons.	DETA to objective sands; show ing points, and al coal septh 507; r Point Lookou - 4000', and a ,000# sand. In ing pressure 7;	AILS OF WOI sizes, weights, and led to ther important property. Perspore to perforate \$602' - 4508 reakdown presport. Inject	ngths of proposed casing opposed work) ry bridge plug d intervals 47 ' (4 holes/ft. seure 700, mail ion rate 64 bb.	at 4050'. 54' - 4760',) with 100,400 ximus pressure 1s /sin. Flush 141956 CON. COM.

i i

as well littled