

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION	<b>X</b>	REPORT ON (Other)	

June 7, 1954  
(Date)

Farlington, New Mexico  
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

AZTEC OIL AND GAS COMPANY  
(Company or Operator)

Dusenberry  
(Lease)

H. B. Lynn Drilling Company  
(Contractor)

Well No. 2 in the NW 1/4 SE 1/4 of Sec. 1

T. 31-N, R. 12-W, NMPM, Blanco-La Plata Pool, San Juan County.

The Dates of this work were as follows: May 17, 1954 through May 23, 1954

Notice of intention to do the work (was) ~~submitted~~ submitted on Form C-102 on April 13, 1954  
(Cross out incorrect words)

and approval of the proposed plan (was) ~~obtained~~ obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

May 17, 1954 - Set 761' of 5-1/2" Liner at 5170 and cemented with 475 sacks, top of liner 4404. Ran HOWCO Retrivable Cementer set at 4385 and squeezed with 75 sacks.  
May 18, 1954 - Squeezed top of liner with 150 sacks - Reached maximum of 3000#  
May 19, 1954 - Blowing to bottom with gas after squeezing top of liner  
May 20, 1954 - Drilling cement - cleaning out to 5187  
May 22, 1954 - Sand Oiled with 11,000 gals. oil & 5900# sand - treating pressure 2100# - 356 gallons per minute.  
May 23, 1954 - Ran 180 joints of 2" Tubing set at 5390  
May 24, 1954 - Gauged 2230 MCF 2 1/2 hours after treatment.

Witnessed by Hurchel H. Williams Astec Oil & Gas Company Drilling Superintendent  
(Name) (Company) (Title)

Approved: OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name H. H. Williams

Position Drilling Superintendent

Representing AZTEC OIL & GAS COMPANY

Address 112 North Behrend - Farlington, N.M.

Oil and Gas Inspector Dist. #3.  
(Title)

(Date)

OIL CONSERVATION COMMISSION	
AZTEC DISTRICT OFFICE	
No. Copies Received	3
DISTRIBUTION	
Comptroller	/
General	/
Executive	
Secretary	
U.S.G.P.	
Inspector	
File	/