Form 9-331 b
(April 1952)

	X		

(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R359.4.
Approval expires 12-31-60.

Indian Agency Navajo

Allottee

Lease No. 14-20-603-[illegible]

Co. Lse. No. [illegible]

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

ILLEGIBLE

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL		SUBSEQUENT REPORT OF REDRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		~~SUPPLEMENTARY WELL HISTORY~~ Subsequent Report of Perforating	
NOTICE OF INTENTION TO ABANDON WELL		and Fracture Treatment	X

RECEIVED
U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Navajo Tribe "P"

Farmington, New Mexico July 14, 1959

Well No. 25 is located 660 ft. from {N/S} line and 1980 ft. from {E/W} line of sec. 4

NE/4 of NW/4 Sec. 4 (¼ Sec. and Sec. No.) T-31-N (Twp.) R-17-W (Range) NMPM (Meridian)

Chimney Rock Gallup (Field) San Juan (County or Subdivision) New Mexico (State or Territory)

The elevation of the derrick floor above sea level is [illegible] ft. Gr.

RECEIVED
JUL 17 1959
OIL CON. COM.
DIST. 3

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Spudded 9-5/8" hole at 3:00 P.M., 6/22/59. Set 7-5/8" casing at 48' w/8 sacks reg. cement. Drilled w/air to 1085' & mudded up. 1107' TD, 1102 PBD. Ran elec. logs. Set 5" OD casing at 1105' w/75 sacks [illegible] cement. Pumped plug down w/200 gals. MCA & oil. Ran Gamma Ray & Collar Logs. Perforated from 1030' to 1040' w/2 jet shots per foot. Sand/Oil frac w/20,000 gals. lse. crude, 20,000# sand & 400# FLA. Ave. Inj. Rate 16 bbls./min. at 900#. Pumped out sand from 1055'. Set 2" tubing at 1029'. Ran rods & pump and set pumping unit. On final 24 hour potential test on 16-32" SPM pumped 77 bbls. new oil. Corr. Gr. 39.3. First new production July 12, 1959.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Humble Oil & Refining Company

Address Box 1166
Farmington, New Mexico

By Russell M. Lilly

Title District Superintendent

U. S. GOVERNMENT PRINTING OFFICE 16—8437b-8