

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well
2. NAME OF OPERATOR
W.M. Gallaway
3. ADDRESS OF OPERATOR
101-2 Petroleum Plaza Bldg. Farmington, N.M.
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 2020'FNL, 1980'FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

SUBSEQUENT REPORT OF:

RECEIVED

AUG 19 1981

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

5. LEASE
14-20-151-45
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
UTE MOUNTAIN INDIAN
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
UTE INDIAN
9. WELL NO.
1-B
10. FIELD OR WILDCAT NAME
VERDE GALLUP
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
SEC. 4, T31N, R15W
12. COUNTY OR PARISH
San Juan
13. STATE
N.M.
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5866GR

(Note: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5/13/81 Filled hole w/gel water, circulated w/45 tubing sub.
Spotted 14 sks. cement across Gallup perfs. 2112'-2014'
and continue up inside 4½" casing 50'

5/14/81 Tagged top of cement 1960', Stretched casing parted @ 912'
Spotted 15 sks cement across 4½" csg. stub 937'-888'
Spotted 25 sks cement across top of Point Lookout 430'-330'
Spotted 20 sks cement across bottom of surface

5/28/81 Spotted 10 sks cement top of csg., erect dry hole marker and clean location.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

