

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

RECEIVED JUN 21 1992 OIL & GAS DIV SUNDY 1. Type of Well GAS 2. Name of Operator Meridian Oil Inc. 3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700 4. Location of Well, Footage, Sec., T, R, M 860'FNL, 1610'FWL Sec.3, T-31-N, R-12-W, NMPM, San Juan County	API # (assigned by OCD) 5. Lease Number 6. State Oil&Gas Lease Fee 7. Lease Name/Unit Name Decker A 8. Well No. 2 9. Pool Name or Wildcat Basin Dakota 10. Elevation: 6108'GR
---	--

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☒ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☒ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

06-11-92 MOL&RU. Blow down. ND WH. NU BOP. TOOHH w/tbg & Model R pkr. Ran 4 1/2" gge ring to 7220'. Set cmt ret @ 7218'. PU FBP, test tbg in hole to 2500#. SDFN.

06-12-92 Set pkr @ 6987'. Load backside w/2% KCl wtr. PT 1500#/30 min, ok. Swab Dk perfs 7061-7180'. SDFN.

06-13-92 TOOHH w/pkr. TIH w/tbg blowing down. SDFN.

06-14-92 Logged off. Flow to pit. Blow to pit. SD for weekend.

06-15-92 Blow to pit. Sting into cmt ret @ 7218'. No press under ret. Squeeze Morrison perf's 7231-35' w/15 sx Class "B" neat cmt w/2% calcium chloride. TOOHH w/sting. WOC. SDFN.

06-16-92 Rig idle for repairs

06-17-92 CO to 7067'. Drl cmt to 7168'. Flow to pit.

06-18-92 Rig repairs.

06-19-92 Blow to pit. SDFN.

06-20-92 TIH, set cmt ret @ 7093'. Sting into ret. Est rate 1.5 BPM 1200 psi. Squeeze Dakota perfs w/16 sx Class "B" neat cmt. Sting out of ret. Spot 4 sx cmt on top of ret. TOOHH to 6292'. Load csg w/60 BW, circ btms up. Spot 16 sx cmt. Fill csg 6292-6192'. TOOHH to 4153'. Spot 16 sx cmt. Fill csg 4153-4053'. TOOHH to 2546'. Spot 44 sx cmt. Fill csg 2546-1994'. TOOHH w/tbg. Shot 2 holes @ 800'. Est rate @ 2.2 BPM @ 600 psi, good circ out bradenhead. Pump 266 sx Class "B" cmt, circ 3 bbl. to pit. ND BOP. Cut off WH. Install dry hole marker. Well plugged & abandoned.

SIGNATURE *James Bradfield* Regulatory Affairs June 22, 1992

(This space for State Use)

Approved by Original Signed by CHARLES O'NEALSON

Title

Date JUL 01 1992

OPERATOR