

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

990' FSL, 990' FWL, Sec. 32, T-32-N, R-9-W, NMPM, San Juan County

API # (assigned by OCD)

30-045-11130

5. Lease Number

State Oil & Gas Lease #

E-178-10

7. Lease Name/Unit Name

San Juan 32-9 Unit

8. Well No.

7

9. Pool Name or Wildcat

Blanco Mesaverde

10. Elevation:

Type of Submission

Type of Action

☐ Notice of Intent	☒ Abandonment	☐ Change of Plans
☐ Subsequent Report	☐ Recompletion	☐ New Construction
☐ Final Abandonment	☐ Plugging Back	☐ Non-Routine Fracturing
	☐ Casing Repair	☐ Water Shut off
	☐ Altering Casing	☐ Conversion to Injection
	☐ Other -	

13. Describe Proposed or Completed Operations


7-28-98 MIRU. ND WH. NU BOP. Release Model "R" pkr. SDON.

7-29-98 TOO H w/pkr & 191 jts 2 3/8" tbg. TIH w/5 1/2" CIBP, set @ 5616'. TOO H. TIH tag CIBP @ 5616'. Load hole w/190 bbl wtr. PT csg to 1000 psi, failed. Plug #1: pump 46 sx Class "B" neat cmt inside csg @ 5280-5616'. TOO H. TIH, tag TOC @ 5280'. TOO H to 3726'. Perf 3 sqz holes @ 3726'. TOO H. TIH w/7" cmt retainer, set @ 3672'. Establish injection w/18 bbl wtr. Plug #2: pump 26 sx Class "B" neat cmt below cmt retainer outside csg. Pump 29 sx Class "B" neat cmt inside csg @ 3585-3672'. TOO H. SDON.

7-30-98 Load csg w/18 bbl wtr. Attempt to PT csg, failed. TIH, tag TOC @ 3610'. Perf 3 sqz holes @ 3305'. TOO H. TIH w/7" cmt retainer, set @ 3255'. TOO H. TIH, establish injection w/15 bbl wtr. Plug #3: pump 26 sx Class "B" neat cmt outside csg below cmt retainer @ 3205-3305'. Pump 29 sx Class "B" neat cmt inside csg. TOO H. TIH, perf 3 sqz holes @ 2210'. TOO H. TIH w/7" cmt retainer, set @ 2160'. Establish injection. Plug #4: pump 40 sx Class "B" neat cmt outside csg @ 2055-2210'. Pump 40 sx Class "B" neat cmt inside csg. TOO H. TIH, perf 3 sqz holes @ 222'. Establish circ down csg & out bradenhead w/14 bbl wtr. Plug #5: pump 127 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.

7-31-98 ND BOP. Cut off WH. Fill 7" csg & 7" x 9 5/8" annulus w/20 sx Class "B" neat cmt. Install dry hole marker w/20 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 7-31-98.

SIGNATURE
no



Regulatory Administrator August 14, 1998

(This space for State Use)

ORIGINAL SIGNED BY E. VILLANUEVA

DEPUTY OIL & GAS INSPECTOR. DIST. #3

SEP 28 1999

Approved by

Title

Date