

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Santa Fe
Lease No. 079381
Unit San Juan 32-8 Unit
14-02-001-446

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Fracture</u> X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

March 26, 1956

Well No. 14-34 is located 1670 ft. from S line and 1530 ft. from W line of sec.SW Section 34 32N 8W : 14E
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Blanco San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 6660 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

3-23-56 Total Depth 6075'. Water fractured Point Lookout perforated intervals 5896-5910, 5933-5943, 5972-5989 with 51,269 gallons water and 55,000# sand. Breakdown pressure 1900#, max. pressure 1900#, avg. treating pressure 1800#. Injection rate 46.8 bbls./min. Flush 6045 gallons. Natural gas none.

3-25-56 Total Depth 6075'. PBID 5875'. Water fractured Menefee perforated intervals 5724-5732, 5736-5744, 5832-5840, 5846-5856 with 49,345 gals. water and 55,000# sand. Breakdown pressure 1750#, max. pressure 2250#, avg. treating press. 1800#. Injection rate 44.8 bbls./min. Flush 7251 gallons. Natural gas none.

3-25-56 Total Depth 6075'. PBID 5648'. Water fractured Cliff House perforated intervals 5552-5558, 5600-5610, 5621-5633 with 49,962 gallons water & 55,000# sand. Breakdown pressure 1950#, max. pressure 2250#, avg. treating press. 2100#. Injection rate 45.8 bbls./min. Flush 7300 gallons. Natural gas none.

Company El Paso Natural Gas CompanyAddress Box 997Farmington, New MexicoBy D. L. EdwardsTitle Petroleum engineer