3-M.M.O.C.C. Astec 1-Bill Cutler 1-Gliver Fowler 2-L. D. Galloway 1-File

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Elanco For			rmation_	mation Mess Verde				County San Juan			
Init	ial 🗶	An	nuzi		Spec	ial		_Date of	Test	9-30-57		
Comp	oany Pacific	Northwest	t Pipaline	L	ease_S	an Juan	3 2- 9	Wel	.1 No	53-27		
Unit	7-5/8"	Sec. <u>27</u>	Iwo . 321	Rge.	. <u>94</u>	Purc	haser	Not con	nected			
Casi	7-5/8" ing_5_}" W	/t	I.D.	Set	at_62	72¹ 55¹Pe:	rf 5	6721	То	62341	·	
Tubing 1-1/4 Wt. I.D. Set at 6189 Perf. To												
Gas Pay: From 5672' To 6234' L xG est.650 -GL Bar.Press.												
Producing Thru: Casing Tubing Type Well Single Single-Bradenhead-G. G. or G.O. Dual												
Date of Completion: Packer Single-Bradenhead-G. G. or G.O. Dual Reservoir Temp.												
						ED DATA						
Test	ed Through	(Description)	(Choke)	Xex BEST	Shart	t in 7 de	A.	Туре Тар	s			
	Flow Data			Tubir			Data	Casing D	Data			
No.	(Prover) (Line)	(Choke) (Orifice			- 1	Press.	-	Press.		Durati of Fl		
SI	Size	Size	psig	h _w	°F•		°F.	psig	°F∙	Hr.		
1.		3/4"B.K.	1.84		73°	977 247		100.0		shut 1		
2. 3.												
4. 5.												
				FI	OW CAL	CULATIONS	5					
No.	Coefficient Pres				sure Flow Temp. Gravit Factor Factor			ty Compress. Rate of Flow Cor Factor Q-MCFPD				
			wpf I	osia	Ft		Fg	F _p v		@ 15.025 psia		
1. 2. 3. 4.	18.1605			96	.9877		.9608	1	.01. 8	2681		
3. 4.												
5.	·											
				PRES	SSURE CA	ALCU ATI	ONS		*			
	iquid Hydro ty of Liqui		bons		f/bbl.deg.					arator Gas wing Fluid_		
'c		· · · · · · · · · · · · · · · · · · ·	(1-e ^{-s})					1692	_P ²	1,044,484		
- T	$P_{\mathbf{w}}$											
No.	Participal	$P_{\mathbf{t}}^2$	F _c Q	$(F_cQ)^2$	(F ₀	cQ) ² -e ^{-s})	P _w 2	$P_c^2 - P_w^2$	Cá	P _w P _c		
1.	259				+ ``			977,40	3	1.0	686	
1. 2. 3. 4.												
5.					<u> </u>				<u> </u>			
Abso	lute Potent ANY Pacif	ial:	818	ne Corne	MCFPD;	n	75/ 1.051	L——				
ADDR	ESS 405 W	est Broads	ay, Jami	ngion, I	ev Kerci	CO		/	XLL	HYLD \		
WITN	ESSED		Adams - E							L 4002		
COMP	ANY	. R. Pas	d Fractor	Ges Com	REM	ARKS			-	N. COM. ST. 3		
								•	V 01			

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q = Actual rate of flow at end of flow period at W. H. working pressure (Pw). MCF/da. @ 15.025 psia and 600 F.
- P_c= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- Fpv Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERV	ATION COMMISSION
	OFFICE
No. Copies Ria	
year on	
DE PORCE	
Sec Fe :	
O Beating from	***
State Lund (1900	
1503	
Transporter	The same of the same specific and the same s
File	1 1