NOTICE OF INTENTION TO DRILL	SUBSEQUENT RE	PORT OF WATER SHUT-OFF RECEIVE
NOTICE OF INTENTION TO CHANGE PLANS		PORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO TEST WATER S		PORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR	REPAIR WELL SUBSEQUENT RE	PORT OF RE-DRILLING OR HEPSIRGEDE OF CAL-SU
NOTICE OF INTENTION TO SHOOT OR AC	IDIZE SUBSEQUENT RE	PORT OF ABANDONMENT FARMINGTON, NEW ME
NOTICE OF INTENTION TO PULL OR ALTE	ER CASING SUPPLEMENTAR	Y WELL HISTORY
NOTICE OF INTENTION TO ABANDON WEL		
(INDICATE A	ABOVE BY CHECK MARK NATURE OF REPORT, N	IOTICE OR OTHER DATA)
(11-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1		,,
		May 5 , 1958
	(~)	227 ft. from E line of sec. 28
1E Sec. 25 (4 Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)
	Con Sport	Mana Marrico
(Field)	(County or Subdivision)	(State or Territory)
ate names of and expected depths to ob,	DETAILS OF WORK	hs of proposed casings; indicate mudding jobs, cement-
State names of and expected depths to ob		hs of proposed casings; indicate mudding jobs, cement-
4-29-58. Total Depth 6 perforated intervals 58 5060-6072; 6082-6094; 6 sand. B.D.P. Hone, nax	jective sands; show sizes, weights, and length ing points, and all other important proposed in the same state of the sam	8'. Water fractured Point Looko h-6014; 6032-6051 w/2 shots/ft.; h 87,000 gallons water and 90,00 1350-1600-1800-2200#. I.R. 57
Junderstand that this plan of work me company El. Paso Ratura address Box 937	jective sands; show sizes, weights, and length ing points, and all other important proposed. 195'. Plug back T.D. 615 64-5904 w/l shot/ft.; 599 108-6146 w/l shot/ft. with the pr. 2350%, evg. tr. pr. Dropped 5 sets of 15 ball ust receive approval in writing by the Geological Gas Company	8. Water fractured Point Looks k=6014; 6032-6051 w/2 shots/ft.; h 87,000 gallons water and 90,00 1350-1600-1800-2200 . I.R. 57
1 understand that this plan of work me company	jective sands; show sizes, weights, and length ing points, and all other important proposed. 195'. Plug back T.D. 615 64-5904 w/l shot/ft.; 599 108-6146 w/l shot/ft. with the pr. 2350%, evg. tr. pr. Dropped 5 sets of 15 ball ust receive approval in writing by the Geological Gas Company	8. Water fractured Point Locko 4-6014; 6032-6051 w/2 shots/ft.; h 87,000 gallons water and 90,00 1350-1600-1800-2200 I.R. 67