

**NEW MEXICO OIL CONSERVATION COMMISSION**  
Santa Fe, New Mexico

**MISCELLANEOUS NOTICES**

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

**Indicate Nature of Notice by Checking Below**

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) <b>Repair Well</b>	<b>XX</b>

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Farmington, New Mexico  
(Place)

June 8, 1964  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

El Paso Natural Gas Company Fields Well No. 1 in A (Unit)  
(Company or Operator)  
NE 1/4 NE 1/4 of Sec. 25, T. 32N, R. 11W, NMPM, Blanco Mesa Verde Pool  
(40-acre Subdivision)  
San Juan County.

**FULL DETAILS OF PROPOSED PLAN OF WORK**

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Due to a casing leak & the bradenhead making gas & water it is intended to repair this well in the following manner:

If tubing can be pulled -

Pull tubing & set top drillable bridge plug at approximately 4680'.  
Perf. squeeze holes at 2980' & squeeze w/100 sks. cement.  
Perf. squeeze holes at 2000' & squeeze w/100 sks. cement.  
Drill out bridge plug & clean out to 5390'.  
Run full string of 4 1/2" casing & cement, bringing cement up into 7" casing.  
Perf. & frac Mesa Verde & complete well.

If tubing cannot be pulled -

Cut tubing off below 7" casing & pull.  
Set cement retainer at approximately 4680' & squeeze open hole.  
Perf. & squeeze as above.  
Drill out retainer, set whipstock & drill to 5390'.  
Complete as above

**JUN 10 1964**

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By Original Signed Emery C. Arnold

Title Supervisor Dist. # 3

El Paso Natural Gas Company  
Company or Operator

By OR. G. NAL SIGNED E. S. OBERLY

Position Petroleum Engineer

Send Communications regarding well to:

Name E. S. Oberly

Address Box 990, Farmington, New Mexico

