


Corrected Copy

Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office Santa Fe  
Lease No. 078507  
Unit San Juan 32-9 Unit  
14-08-001-569

## SUNDRY NOTICES AND REPORTS ON WELLS

|   |   |          |
|---|---|----------|
| NOTICE OF INTENTION TO DRILL.....                   | SUBSEQUENT REPORT OF WATER SHUT-OFF.....        |          |
| NOTICE OF INTENTION TO CHANGE PLANS.....            | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... |          |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....     | SUBSEQUENT REPORT OF ALTERING CASING.....       |          |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... |          |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....        | SUBSEQUENT REPORT OF ABANDONMENT.....           |          |
| NOTICE OF INTENTION TO PULL OR ALTER CASING.....    | SUPPLEMENTARY WELL HISTORY.....                 |          |
| NOTICE OF INTENTION TO ABANDON WELL.....            | <u>Water Fracture</u>                           | <u>X</u> |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 7, 1956

Well No. 39 is located 800 ft. from N line and 1490 ft. from E line of sec. 26NE Section 26 32N 10E 10EPM  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)Blanco San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)The elevation of the derrick floor above sea level is 6959 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

10-14-56 T.D. 6259'. Plug back T.D. 6211'. Water fractured L. P int Lockout perf. int. 6154-60, 6170-80, 6187-97 w/32, 286 gals. water &amp; 10,000# sand. MDP 2100#, max. pr. 3000#, avg. tr. pr. 2500#, Inj. rate 50 BPM. Flush 8000 gallons.

10-15-56 T.D. 6259'. Temp. B.P. @ 6143'. Water fractured U. Point Lockout perf. int. 6071-83, 6101-11, 6122-32 w/56, 180 gals. water &amp; 47,000# sand. MDP 1950#, max. pr. 1800#, avg. tr. pr. 1800#. Inj. rate 55.8 BPM. Flush 7000 gallons.

10-15-56 T.D. 6259'. Temp. B.P. @ 5800'. Water fractured Cliff House perf. int. 5658-68, 5688-5702, 5714-20 w/59, 180 gals. water &amp; 60,000# sand. MDP 1500#, max. pr. 1800#, avg. tr. pr. 1800#. Inj. rate 57.5 BPM. Flush 6000 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas CompanyAddress Box 997Farmington, New MexicoBy W. F. CorralTitle Petroleum Engineer

1914

1915

1916

1917

1918

1919

1920

1921

1922

1923

1924

1925

1926

1927

1928

1929

1930

1931

1932

1933

1934

1935

1936

1937

1938

1939

1940

1941

1942

1943

1944

1945

1946

1947

1948

1949