


(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lesse No. 070472  
Unit San Juan 32-7 Unit



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 31, 1963

Well No. 39(MD) is located 1650 ft. from [S] line and 1840 ft. from [W] line of sec. 23

SW/4 Section 23  
(1/4 Sec. and Sec. No.)

T-32-N, R-7-W  
(Twp.) (Range)

N.M.P.M.  
(Meridian)

Blanco MV Basin Dakota  
(Field)

San Juan  
(County or Subdivision)

New Mexico  
(State or Territory)

The elevation of the derrick floor above sea level is 6603 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled to 8074' 7-23-63. Ran 219 joints 5 1/2" casing (62 joints 17#, 2012.49'; 53 joints 15.5#, 2167.95'; 11 joints 17#, 355.45'; 65 joints 15.5#, 2368.44'; 28 joints 17#, 1139.01') 8054' set at 8043' OL. Cemented w/445 sacks 50/50 Diamix, 4% gel, 1/4# fine tufplug/sk., & 1/8# floccle/sk., 0.4% R-5 followed by 50 sacks neat. PD @ 3:45 A.M. 7-24-63. 40 barrels gel water ahead of cement.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 990

Farmington, New Mexico

By OR G NAL SIGNED E. S. OBERLY

Title Petroleum Engineer