

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF - 078039 - A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Primo Ridge #1

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Blanco Mountains

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 24, T-32N, R-11W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6352 DF

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved on and rigged up workover 10/20/65.

Pulled tubing.

Cleaned out to 5616.

Ran 171 joints of 4 1/2" casing set at 5595.

Ran 350 sacks of class "c" cement, 8 1/2 gal, 3/4 floccal per sack, 150 sacks of class "c" cement, 4 1/2 gal, 3/4 per sack floccal mixed, 100 sacks class "c" cement with 2% calcium chloride, 6/10 of 1 1/2 Haled 9.

Ran temperature survey - found cement top at 5050.

Shot 4 holes at 4968-69, squeezed with 400 sacks cement.

Perforated 5462-62, 5437-27, 5408-02, 5358-52, 4994-75, 4964-59, 4943-37, 2 shots per foot.

Frac with 40,000# 20/40 sand, 20,000# 10/20 sand, Fr-8, 3 1/2# per 1000 gallons, dropped 120 balls.

Ran 177 joints of 2-3/8" tubing set at 5494.

Rigged down 11/7/65.

Potential test - SICP - 820, SITP - 880

FCP - 487, FTP - 226

3/4" potential - 2800 MCF ACP - 3911 MCF

18. I hereby certify that the foregoing is true and correct

SIGNED ORIGINAL SIGNED BY JOE C. SALMON TITLE District Superintendent

DATE 12/29/65

(This space for Federal or State office use)

APPROVED BY 20
CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

RECEIVED

DEC 30 1965

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.