

submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED
MAIL ROOM

Sundry Notices and Reports on Wells PH12: 20

1. Type of Well
GAS

2. Name of Operator
MERIDIAN OIL

3. Address & Phone No. of Operator
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M
1840' FSL, 990' FWL, Sec. 19, T-32-N, R-9-W, NMPM

5. Lease Number
SF-078513
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
San Juan 32-9 Unit
8. Well Name & Number
San Juan 32-9 U #59
9. API Well No.
30-045-11338
10. Field and Pool
Blanco Mesaverde
11. County and State
San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
☐ Notice of Intent	☒ Abandonment
☒ Subsequent Report	☐ Recompletion
☐ Final Abandonment	☐ Plugging Back
	☐ Casing Repair
	☐ Altering Casing
	☒ Other - Pay add
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Fracturing
	☐ Water Shut off
	☐ Conversion to Injection

13. Describe Proposed or Completed Operations

11-28-95 MIRU. ND WH. NU BOP. TOO H w/50 jts 2 3/8" tbg. TIH w/fishing tools to recover rest of 2 3/8" tbg. Tag fish @ 1616'. Ran overshot to 2792' before tagging up solid. TOO H. TIH w/skirted mill.

11-29/30-95 Fishing. (Verbal approval to plug and abandon from Wayne Townsend, BLM on 11-30-95).

12-1-95 TIH w/7 5/8" cmt retainer, set @ 2702'. Load annulus w/120 bbl wtr. Establish injection. Can not get good enough rate to cmt below cmt retainer. (Verbal approval to change plans from Wayne Townsend, BLM). Plug #1: pump 55 sx Class "B" cmt on top of cmt retainer @ 2702'. Reverse out cmt. TOO H to 1700'. Perf 4 sqz holes @ 1922'. TIH w/cmt retainer, set @ 1701'. Establish injection. Plug #2: pump 180 sx Class "B" cmt below cmt retainer, 3 bbl Class "B" cmt on top of cmt retainer. TOO H. Perf 4 sqz holes @ 615'. Attempt to establish circ out bradenhead, failed. Plug #3: pump 65 sx Class "B" cmt down csg. WOC. TIH, tag TOC @ 411'. TOO H. Perf 4 sqz holes @ 230'. Establish circ down csg & out bradenhead. Plug #4: pump 200 sx Class "B" cmt down csg & out bradenhead. Circ 5 bbl cmt to surface. RD. ND BOP. Cut off WH. Install dry hole marker w/10 sx Class "B" cmt. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Administrator Date 12/4/95

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

Approved as to planning of the well and
facility under there is related to the
Bureau of Land Management

NMOCD

APPROVED

REC'D
DISTRICT MANAGER