Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Poo	1	Blanco				Formation Mesa Verde				County San Juan			
						Special							
Com	pany	PACIFIC NORTHWEST PI			r PIPEL	PELINE Lease N.M. 32-11			1	Well No			
Unit A Sec19 Twp32N Rge11W Purchaser Not Connected													
Casing 53" Wt. 14.04 I.D. Set at 5720' Perf. 5682' To 5016'													
<b>Tu</b> b	ing	11 W	t	2 <b>.3</b> #_I	•D•	Se	t at <b>5</b> (	<b>576'</b> Per	rf	·	То		
Gas Pay: From To L xG .650 -GL Bar.Press. 12													
Pro	Producing Thru: Casing Tubing x x Type Well Single Single-Bradenhead-G. G. or G.O. Dual												
Date	Date of Completion: Packer Reservoir Temp.												
								ED DATA					
Test	ted Th:	rough	(Ptó)	tét) ((	Choke)	(Métét)	Shut :	in 7 days	l.	Type Tap:	s		
			Flow Data					Tubing Data		Casing Data			
,,_	(Pro	over)	(Cho	oke)	Press.	Diff.	Temp.	Press.		Press.			
No.		ine) ize	(Ori	fice) ize	psig	h <sub>w</sub>	$\circ_{\mathtt{F}}.$	psig	°F.	psig	∍ <sub>F</sub> .	of Flow Hr.	
SI			<u> </u>					1055		1066			
1.					140		57	140	57°	1026		3 hours	
2 <b>.</b> 3.					<b> </b>								
4.						.,							
5.													
				<b></b> .			FLOW CAL	CULATIONS	S				
.,	Coefficient			Pr	Pressure Flow Temp. Gravit								
No.	(24-Hour)		r)	n n				tor Factor				Q-MCYPD @ 15.025 psia	
<del>-</del> -							Ft 110029		Fg	F <sub>pv</sub>			
1. 2.		12.3650				152 11		.9608		1.414		1836	
3。													
4. 5.													
5.	<del></del>	-								_			
PRESSURE CALCULATIONS  Gas Liquid Hydrocarbon Ratio cf/bbl. Specific Gravity Separator Gas  Gravity of Liquid Hydrocarbons deg. Specific Gravity Flowing Fluid  C													
No.	P <sub>w</sub>	osia)	Pt	E F	,Q	(F <sub>c</sub> Q) <sup>2</sup>	(F.	Q) <sup>2</sup> -e-s)	<b>1038</b> P <sub>w</sub> 2	$P_c^2 - P_w^2$	F	Pw Pc	
1. 2.				_			<del></del>		1077.4	84.7	4	13.72	
3.			<del></del>										
3. 4. 5.				_							<del> </del>		
Absc	olute I	Potent:	ial:_	11,	237		MCFPD;	n	.75/ 6.:	1201			
	PANY	PACTE	IC_HOS	PINNESS	PIPEL	THE COR	ORATION						
ACEN	TESS VT and	TTTLE	ilest_	proedu	y, Jar	mington,	New Mer lest Rog	deo	<del></del>	·····		9/7	
WITN	NESSED_				70/198			Lucer		/			
					-		REM	ARKS			OCON	(300 Mg)	

## INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

## NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure  $(P_W)$ . MCF/da. @ 15.025 psia and 60° F.
- $P_c$ = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- PwI Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- hw Differential meter pressure, inches water.
- Fg Gravity correction factor.
- Ft Flowing temperature correction factor.
- $F_{nv}$  Supercompressability factor.
- n I Slope of back pressure curve.

Note: If  $P_W$  cannot be taken because of manner of completion or condition of well, then  $P_W$  must be calculated by adding the pressure drop due to friction within the flow string to  $P_{t}$ .