State of New Mexico Energy, Minerals and Natural Resources Department OIL CONSERVATION DIVISION

OIL CONSERVATION DIVISION					
Sundry Notices and Reports on Wells					
1. Type o	f Well GAS	MAY3 0 199	W	5.Type o	
Meridia 3. Address PO Box 4. Well Lo		ngton, NM 8749		7.Lease Bonds 8.Well N ty 9.Pool N	Name/Unit Name o. 1 ame or Wildcat o Mesa Verde
10.Elevati	ions 'GR				
11.Intent	to/Subsequer	nt Report of :		workove	r
12.Describ	pe proposed o	or completed ope	erations:		
MOL&RU. Blew well down. Kill well w/1% KCl wtr. NDWH. NU BOP. TOOH w/tbg. TIH, tag fish. TOOH w/tbg & fish. SDFN. Killed well w/1% KCl wtr. TIH w/tbg, bit & scraper to 5192'. TOOH. TIH, set BP @ 4744'. Load 5 1/2" csg. PT 1000#/15 min, ok. ND BOP. Removed tbg hanger. Loaded annulus. TIH w/5 1/2" csg spear, pulled 80,000#, no movement. Pulled 120,000#, none. Released csg spear. NU BOP. SDFN.					
05-09-90 05-10-90	covered. Cut off lip. Stacked out on 5 1/2". Loaded hole, closed blind rams. PT 1000#, bled back to 600# in 3 min. NMOCD witnessed. Ran CCBL. Fould collar @ 1520'. Pulled 35,000# on csg, set off shot. Unscrewed csg, pulled up 5', ran CCL- showed 5' gap. Pull cutoff jt. Set slips, placed 5 1/2"to2" swedge and 2" valve in csg. Closed valve & rams. SDFN.				
SIGNATURE	1400'. Pump RBP @ 1490'	ed into perf. E	Broke circ t	o surface BP. SDFN.	out BH. TIH, set (cont'd on back) S-25-90 Date
				:	

(This space for State use)

APPROVED BY Original Signed by FRANK I. CHAVEZ
CONDITION OF APPROVAL, IF ANY:

THE STATE OF THE S

DATE JUN 0 1 1990

TITLE

Bonds #1 - Page Two

- TIH to 1450'. PT BP & csg 1000#. Released pkr, pulled up to 1200', broke circ out BH. Squeezed w/100 sx Class "B" 65/35 Poz, 6% gel, 6.25# gilsonite, 2% calcium chloride, tail w/300 sx Class "B" w/2% calcium chloride. Circ cmt to surface. Attained squeeze of 1000# w/10 sx left in csg. Released pkr, reversed tbg clean, reset pkr. PT 1000#. SDFN.
- O5-12-90 Released pkr. TOOH w/tbg & FBP. TIH tag cmt @ 1358'. Drld squeeze. Circ hole clean. PT 1000#/15 min, ok. TOOH. TIH, tag sand on top of RBP, rerversed clean. TOOH w/BP. SD for Sunday.
- 05-14-90 Run 5 1/2" csg. ND BOP. NU WH. Ran GR, CCL, CBL 1350-4700', SDFN.
- O5-16-90 Perf'd, @ 2670'. Ernie Bush, NMOCD approved squeeze as planned. Rih w/ 2 3/8" tbg, 5 1/2" FBP. Set pkr @ 2407', pressure backside to 750 psi. RU Western, estab circ @ 2 1/2 bbls/min @ 175#. Squeezed perf's w/275 sx "B" w/2% KCL on tail 40 sx. Cmt to surface w/all cmt. Closed bh, squeezed perf to 1450#, left 14 sx in csg. Released pkr & circ tbg clean. Reset pkr & re-pressure squeeze to 1000#. SDON.
- Released pkr. TIH, tagged cmt @ 2562', broke circ, drilled squeeze. Circ hole clean. TIH to top DPB @ 4744', drld plug & pushed to btm. TOOH w/bit, scraper & tbg. TIH w/tbg & exp chk. Tagged remains of DPB @ 5100', circ down to 5170'.

 Landed 2 3/8" tbg @ 5144'. ND BOP, NU WH. dropped ball & pumped out exp chk, unloaded csg w/N2. Shut well in. Rig released.