

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

SF-078113

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Conoco, Inc.

3. Address and Telephone No.

10 Desta Dr. Ste 100W, Midland, TX 79705

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1650' FSL & 1650' FWL
Sec. 18, T-32N, R-11W

7. If Unit or CA, Agreement Designation

Fed. Com 14080071161

8. Well Name and No.

Johns Federal No. 2

9. API Well No.

300451142200

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

Sidetrack

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

This well is an open hole, nitroglycerine completion. It is proposed to sidetrack, redrill, case, and fracture complete the Mesaverde formation according to the plan below:

1. Spot 92 sxs cement to place a 400' plug from 5238'-4838' and set a CIBP @ 4550'.
2. Perforate 7" casing @ 3100' and circulate cement to surface (est. 304 sxs).
3. Set whipstock and mill window @ 4500'.
4. Drill to 5900' with air.
5. Run 4-1/2" casing from 5900' to surface and cement up to 3500' in the 4-1/2" & 7" annulus.
6. Fracture complete Mesaverde and return to production.

RECEIVED

JUN 14 1993

OIL CON. DIV

UNIT 2

070 FARMINGTON, NM

93 JUN -7 AM 11:21

RECEIVED
BLM

14. I hereby certify that the foregoing is true and correct

Signed

Title

Sr. Conservation Coordinator

Date

6/3/93

(This space for Federal or State office use)

Approved by

Title

Conditions of approval, if any:

APPROVED

JUN 08 1993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side

NMOCD