


Form 9-881a  
(Feb. 1951)



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Santa Fe  
Lease No. 078454-B  
Unit Allison

SUNDRY NOTICES AND REPORTS ON **WELLS**

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	DEC 20 1957	X
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING		
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING		
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR		
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT		
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY		
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

December 17, 1957

Well No. 12(MD) is located 1625 ft. from N line and 1550 ft. from E line of sec. 14  
NE Sec 14 32N 7W N.M.F.M.  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
N. Los Pinos Dek., Blanco M. V. San Juan New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6657 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 10-24-57 Plug back to 6042'.  
 Ran 28 joints 7 5/8", N-80, 26.40# casing (894') and 123 joints 26.40, J-55 Hydril (5146') for a total of 151 joints (6030') set at 6040' with 125 regular cement, 125 sack Pozmix, 2% Gel; 1/4#/sk. Flocele, followed with 50 sacks Neat cement.  
 Held 1000# 30 minutes.

Top of cement by temperature survey at 3295'.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company  
 Address Box 997  
Farmington, New Mexico  
 By Original Signed D. C. Johnson  
 Title Petroleum Engineer