NEW MEXICO OIL CONSERVATION COMMISSION

Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS

Revised 12-1-55

Pool	Blanco		F	ormation	Mesa	Verde		County	San	Juan
Init	cial XX									
	oany PACIFIC									
	, <u>M</u>									
	ing 5-1" W								То	62381
Tubi	ing 2-3/8" W	/t	I.D	Set	t at	6203' Pe	rf		То	
Gas	Pay: From_	То_		L	x	.G650		·	Bar.Pre	ss. 12
Prod	lucing Thru:	Casing_		Tul	bing	XX	Type We	ell Sin	gle	
Date	of Complet	ion:u	L -29- 57	Packer	r	Sin	gle-Brade Reservo	enhead-G. (oir Temp	G. or G	.0. Dual
Test	ed Through			(Medel)		ED DATA in 9 days		Туре Тар		
	(Prover)	Flow (Choke)		Diff.	Temp.	Tubing Press.	Data Temp.	Casing Daress.		Duration
No.	(Line) Size	(Orifice)	psig		o _F .	p si g	_ '	psig	o _F .	of Flow Hr.
SI	0120	3/4"	- 	T'W		947 206	0	1052		
1. 2.		3/4	200		00	2.00	68	586		3 porte
3.										
4. 5.			_	 						·
No.	Coeffici (24-Hou 12.3650	. ~	w ^P f		Flow	tor t	Gravity	Compres Factor Fpv	r	Rate of Flow Q-MCFPD @ 15.025 psia
1. 2. 3. 4. 5.										
4.										
as L ravi	iquid Hydro ty of Liqui	d Hydrocar			cf/bbl.deg.	ALCU ATI	Speci			rator Gas ing Fluid
No.	P _w P _t (psia)	Pt2	F _c Q	$(F_cQ)^2$	(F (1	cQ) ² -e-s)	598 P _w 2	P _c -P _w ²	Ca P	
$\frac{1}{2}$							357.6		174	.7 1.46
3.										<u>i</u>
1. 2. 3. 4. 5.										
Abso COMP ADDR AGEN	Plute Potent PANY PACIFIC ESS 405 2 T and TITLE	NORTHWEST	483 PIPELIA dwey, Fe	E CORPOR	MCFPD; MTION i, New M	erico	75/ 1.32	82	Alli	
COMP					REM	ARKS			IL CON	957 OS:

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q \equiv Actual rate of flow at end of flow period at W. H. working pressure (P_W). MCF/da. @ 15.025 psia and 60° F.
- P_c = 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater. psia
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{w}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{DV} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If $P_{\rm W}$ cannot be taken because of manner of completion or condition of well, then $P_{\rm W}$ must be calculated by adding the pressure drop due to friction within the flow string to $P_{\rm t}$.

OIL CONSERVAT	TON COM	MISSIO
No Separa de la	3	
the secondary of the se		A STATE OF THE PARTY OF T
	er fra Line sur til	0
		a