(SUBMIT IN TRIPLICATE)

17

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Land Office	. Santa Pe
Lease No.	SF-078460
Unit 14.	-08-001-441

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT	
NOTICE OF INTENTION TO RE-DRILL OR REPA	
NOTICE OF INTENTION TO SHOOT OR ACIDIZI	SUBSEQUENT REPORT OF ABANDONMENT AUG 2 19 SURVEY ASING U.S. GEOLOGICAL SURVEY U.S. GEOLOGICAL SURVEY
NOTICE OF INTENTION TO PULL OR ALTER CA	U. S. GEOLUGIAN WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	CARMINGTON, IN-
(INDICATE ABOV	SUPPLEMENTARY WELL HISTORY U. S. GEOLOGICAL SO E BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	July 29, 19.57
	1650 ft. from $\begin{Bmatrix} N \\ S \end{Bmatrix}$ line and 910 ft. from $\begin{Bmatrix} E \\ S \end{Bmatrix}$ line of sec. 17
3E/4 Kil/4 Sec. 17 32 (½ Sec. and Sec. No.)	North (Range) (Meridian)
Blanco Mesa Verde	(County or Subdivision) (State or Territory)
in	DETAILS OF WORK (ve sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, essent to surface. Set 7-5/8"
Propose to drill to 200' casing @ 3750', cement w/200 sx nec	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 ax v/8% gel and 50 ax neat. Set 5-1/2" liner 6 at. d thru perfs using approx 150,000 gals of water. Clean
Propose to drill to 200' casing @ 3750', cement w/200 ex necessary with the court to total depth, set to	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- ing points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 ax v/8% gel and 50 ax neat. Set 5-1/2" liner 6 at. d thru perfs using approx 150,000 gals of water. Clean
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Ness Verde to be fracture out to total depth, set to The E/2 of Section 17, con	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- g points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 sx v/8% gel and 50 sx neat. Set 5-1/2" liner @ at. d thru perfs using approx 150,000 gals of water. Clean whing and complete well.
Propose to drill to 200' casing @ 3750', cement w/200 ex necessary with the court to total depth, set to	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- g points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 sx v/8% gel and 50 sx nest. Set 5-1/2" liner @ at. d thru perfs using approx 150,000 gals of water. Clean whing and complete well.
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Mesa Verde to be fracture out to total depth, set to The E/2 of Section 17, con	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 sx v/8% gel and 50 sx neet. Set 5-1/2" liner set. at. d thru perfs using approx 150,000 gals of water. Clean sping and complete well. ataining 320 acres, is dedicated to this well.
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Nesa Verde to be fracture out to total depth, set to The E/2 of Section 17, com 100% Pacific Northwest	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement- g points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 sx v/8% gel and 50 sx nest. Set 5-1/2" liner @ at. d thru perfs using approx 150,000 gals of water. Clean whing and complete well.
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Mesa Verde to be fractured out to total depth, set to The E/2 of Section 17, com 100% Pacific Northwest Lunderstand that this plan of work must re-	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 ax w/8% gel and 50 ax neat. Set 5-1/2" liner set. d thru perfs using approx 150,000 gals of water. Clean whing and complete well. mataining 320 acres, is dedicated to this well. 1957 SIL CON. COM.
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Ness Verde to be fractured out to total depth, set to The E/2 of Section 17, com 100% Pacific Northwest I understand that this plan of work must re-	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, cament to surface. Set 7-5/8" 150 sx v/8/mel and 50 sx neat. Set 5-1/2" liner at. d thru perfs using approx 150,000 gals of water. Clean whing and complete well. ataining 320 acres, is dedicated to this well. 1957 1958 1957 1957 1957 1957 1958 1957 1957 1957 1957 1958 1957 1957 1958 1957 1957 1958 1957 1958 1957 1958 1957 1958 1958 1957 1958 1958 1958 1959 19
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Mesa Verde to be fracture out to total depth, set to The E/2 of Section 17, com 100% Pacific Northwest Lunderstand that this plan of work must re Company PACIFIC NORTHWEST	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, coment to surface. Set 7-5/8" 150 sx w/8/e mel and 50 sx neat. Set 5-1/2" liner sat. d thru perfs using approx 150,000 gals of water. Clean whing and complete well. attaining 320 acres, is dedicated to this well. 1957 St PIPSLINE CORPORATION
Propose to drill to 200' casing @ 3750', cement w/. 5950', cement w/200 ax new Ness Verde to be fracture out to total depth, set to The E/2 of Section 17, com 100% Pacific Northwest I understand that this plan of work must re Company PACIFIC NORTHWE Address 4053 West Broad	we sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work) and set 10-3/h" casing, coment to surface. Set 7-5/8" 150 sx w/8/c gel and 50 sx nest. Set 5-1/2" liner 6 at. d thru perfs using approx 150,000 gals of water. Clean whing and complete well. ataining 320 acres, is dedicated to this well. 1957 Section of the complete well in the complete well in the complete well in the complete well. Set 9-1/2" liner 6 1957 1958 1957 1957 1957 1957 1958 1957 1957 1958 1957 1958 1957 1958 1957 1958 1957 1958 1957 1958 1958 1957 1958 195

NEW MEXICO OIL CONSERVATION COMMISSION

Well Location and Acreage Dedication Plat

Section A.		D	ate <u>Jul</u>	y 29, 19	57	
Operator Pacific Northwest Pi Well No. 16-17 Unit Letter	Section17	Township	52 N	Range	7 W	NMPM
Located 1650 Feet From	north Line, 910	Feet	From	east		Line
County Ban Juan G. L.	Elevation 6537	Dedicated	Acreage	320	·	_Acres
Name of Producing Formation	Mesa Verde	Pool_Blar	nco			
1. Is the Operator the only ow	ner* in the dedicate	ed acreage out	lined on	the plat	below?	,
Yes x No	tion agreement or ot n	cherwise? Yes	No	. If	answer	
Owner		Land Descr	iption	CEIV	ED	
			-RE	1 T	157 .	
				AUG 2 19 GEOLUGICA NGTON, NE	CHRVEY	
				SENT DEIGH	BUEXIC	
			y. S. !	SECTON, NE	M MILL	
			FARM	GEOLOGICA NGTON, NE		
Section B			• •	ì		
	PACIFIC NOR	THWEST	This is	to certi	fy that	the
1				tion in S		
i	1			s true ar		
<u> </u>	!	29		best of n		
		9	and bel		ny Kilowi	cogo
	 			NORTHWES		
		0	(Operator)	CORPORA	TION
		910'	Origina	l signed b	у.Т.,А	Dugan
			<i>(</i> ке	presenta	(ive)	
	SF-9784	-60		Broadway	, Earmi	ngton,
SECTION	dw 17			Address	New M	exico
OIL CON. COM.			well lo plat in from fi surveys my supe same is	to certication shall be section eld notes made by rvision at true and tof my	nown on B was possible of act me or used that d correct	the clotted tual under the ct to
			Date Cu	rveyed	25 July	1957
			Me	phen H	Ken	-
1		_	Registe	red Prof	ssiona	l
	U.S., D.	1.	Enginee	r and/or	Land Su	ırveyor
			-, -g ·	,		•
O 330 660 990 1320 1650 1980 2310 2	2640 2000 1500	000 500 0	Cartifi	cate No.	808	

(See instructions for completing this form on the reverse side)

INSTRUCTIONS FOR COMPLETION:

- 1. Operator shall furnish and certify to the information called for in Section A.
- 2. Operator shall outline the dedicated acreage for both oil and gas wells on the plat in Section B.
- 3. A registered professional engineer or land surveyor registered in the State of New Mexico or approved by the Commission shall show on the plate the location of the well and certify this information in the space provided.
- 4. All distances shown on the plat must be from the outer boundaries of Section.
- 5. If additional space is needed for listing owners and their respective interests as required in question 3, Section A, please use space below

^{* &}quot;Owner" means the person who has the right to drill into and to produce from any pool and to appropriate the production either for himself or for himself and another. (65-3-29 (e) NMSA 1953 Comp.)