

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

**BURLINGTON
RESOURCES**

OIL & GAS COMPANY

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

1190' FNL, 990' FEL, Sec. 16, T-32-N, R-7-W, NMPM, San Juan County

RECEIVED
MAY 15 1993

OIL CON. DIV.
DIST. 3

API # (assigned by OCD)
30-045-11441

5. Lease Number

6. State Oil & Gas Lease #
E-503-14

7. Lease Name/Unit Name

Allison Unit

8. Well No.
5

9. Pool Name or Wildcat
Blanco Mesaverde

10. Elevation:

Type of Submission

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment

Type of Action

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other -
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut off
☐ Conversion to Injection

13. Describe Proposed or Completed Operations

4-13-98 MIRU. ND WH. NU BOP. SDON.

4-14-98 TOO H w/1270' tbg. Tbg parted. TIH w/fishing tools. TIH w/1 13/16" gauge ring to 5540'. TOO H. TIH w/chemical cutter. Chemical cut tbg @ 5455'. TOO H w/tbg & fishing tools. TIH w/CIBP, set @ 5440'. TOO H. SDON.

4-15-98 TIH to CIBP @ 5440'. Load hole w/97 bbl wtr. Plug #1: pump 56 Class "B" neat cmt above CIBP inside csg @ 4942-5438'. TOO H to 3253'. Reverse circ hole clean. WOC. SDON.

4-16-98 TOO H. TIH, perf 3 sqz holes @ 3290'. Perf 3 sqz holes @ 3190'. TOO H. TIH w/5 1/2" cmt retainer, set @ 3222'. PT tbg to 1000 psi, OK. Establish circ. Plug #2: pump 50 sx Class "B" neat cmt below cmt retainer outside csg @ 3190-3290'. Pump 10 sx Class "B" neat cmt above cmt retainer inside csg @ 3050'. Reverse circ 2 bbl cmt to surface. TOO H. WOC. TIH, tag TOC @ 3042'. TOO H. TIH, perf 3 sqz holes @ 2950'. TOO H. TIH w/cmt retainer, set @ 2900'. SDON.

4-17-98 Establish circ. Plug #3: pump 50 sx Class "B" neat cmt below cmt retainer outside csg @ 2850-2950'. Pump 10 sx Class "B" neat cmt above cmt retainer inside csg @ 2850-2900'. TOO H. TIH, perf 3 sqz holes @ 2320'. TOO H. TIH w/cmt retainer, set @ 2274'. Establish injection. Plug #4: pump 94 sx Class "B" neat cmt below cmt retainer outside csg @ 2105-2320'. Pump 28 sx Class "B" neat cmt above cmt retainer inside csg @ 2105-2320'. TOO H. SD for weekend.

Continued on back

SIGNATURE
no



Regulatory Administrator May 11, 1998

(This space for State Use)

DEPUTY OIL & GAS INSPECTOR, DIST #3

OCT 15 1999

Approved by

ORIGINAL SIGNED BY E. VILLANUEVA

Title

Date

- 4-20-98 TIH, tag TOC @ 2042'. TOOH. TIH. Perf 3 sqz holes @ 855'. TOOH. TIH w/cmt retainer, set @ 792'. Establish injection. Plug #5: pump 70 sx Class "B" neat cmt below cmt retainer outside csg @ 755-855'. Pump 10 sx Class "B" neat cmt above cmt retainer inside csg to 705'. Circ hole clean. TOOH. WOC. TIH, tag TOC @ 450'. Perf 3 sqz holes @ 222'. TOOH. Establish circ down csg & out bradenhead. Plug #6: pump 95 sx Class "B" neat cmt down csg & out bradenhead. Circ 1 bbl cmt to surface. WOC. SDON.
- 4-21-98 ND BOP. Cut off WH. Fill 5 1/2" csg & annulus w/5 sx Class "B" neat cmt. Install dry hole marker w/10 sx Class "B" neat cmt. RD. Rig released. Well plugged and abandoned 4-21-98.