

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

CONOCO INC.

3. Address and Telephone No.

10 DESTA DR. STE. 100W, MIDLAND, TX. 79705-4500 (915) 686-5424

4. Location of Well (Footage, Sec., T. R. M. or Survey Description)

1637' FNL & 1650' FEL

Sec. 13, T-32N, R-11W

5. Lease Designation and Serial No.

SF 078119

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Suter 1X

9. API Well No.

30-045-11445

10. Field and Pool, or Exploratory Area

Blanco Mesaverde

11. County or Parish, State

San Juan, NM

CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Repon

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other

Sidetrack

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracuring

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Repon result of multiple completion on WdI Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well is an open hole, nitroglycerine completion. It is proposed to sidetrack, redrill, case, and fracture complete the Mesaverde formation according to the plan below:

1. A cement plug has already been set from 4755'-4598'.
2. Set a CIBP at 4500'.
3. Perforate 7" casing @ 3150' and circulate cement to surface (340 sxs).
4. Run GR/CBL/CCL across proposed sidetrack interval and from 3150' and up.
5. Set whipstock and mill window @ 4350'.
6. Drill 6-1/4" hole with air to 5764'.
7. Run 4-1/2 casing from 5764' to surface and cement up to 3450' with 160 sxs cement.
8. Cut off 4-1/2" casing @ 3450'.
9. Perforate selected Mesaverde intervals and fracture stimulate.
10. Return well to production.

Copies of this "intent" to sidetrack the Suter 1X have been sent by certified mail (as indicated by the attached mail receipts) to all offset operators as required by NMOCD regulations concerning sidetracked holes.

14. I hereby certify that the foregoing is true and correct

Jerry W. Hoover

Signed

Title Sr. Conservation Coordinator

Date

4/9/97

(This space for Federal or State office use)

Approved by

Title

Date

APR 17 1997

Conditions of approval if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side

NMOCD