

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

42-376119

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR PERCO PETROLEUM CORP.	8. FARM OR LEASE NAME Suter
3. ADDRESS OF OPERATOR P.O. Box 669, Albuquerque, New Mexico	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1615 PUL & 1630 PUL, Sec. 14, T30N., R11W. San Juan County, New Mexico	10. FIELD AND POOL, OR WILDCAT Horne Meadows
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit 6, 14-30N-11W.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6499 GR. 6569 RT	12. COUNTY OR PARISH San Juan
	13. STATE N.Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☒
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETION ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

SUBSEQUENT REPORT OF:

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location, measured and true vertical depths for all markers and zones pertinent to this work.)*

IT IS PROPOSED TO:

Set choke in thg. to allow installation of BOP.
Pull thg. set cement retainer in 7" OD at 5070' KB and squeeze open hole (shot)
w/180 sac Class A w/125/ck Silicate followed by 100 sac Class A
w/25 CaCl.
Set widgetock at 4775' KB and mill window in 7" OD csg.
Csg drill 6 1/2" sidetrack hole to 5700'.
Run induction-Gamma Ray log.
Run 4 1/2" OD, 1045, J-35 csg. from surface to TD and cement w/180 sac
Class C cement w/ 125/ck Silicate and 5 1/2/ck NaCl.
Perforate and sand-water free Point Lockout, Manafee and Cliff House
in three stages.
Clean out, run thg., and test well.

NOTE: Rig moved in and work was started August 20, 1967. Oral approval was
obtained from Mr. John Ward on August 21, 1967.

18. I hereby certify that the foregoing is true and correct

SIGNED

Ronald C. Walker

TITLE

Petroleum Engineer

DATE

8-21-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: