Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED
SEP 10 1968
OIL CON. COM.
DIST. 3

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR: Aztec Oil and Gas Co.

3. ADDRESS OF OPERATOR: Drawer 570, Farmington, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface: 990 FSL & 920 FWL, Sec. 28-31N-12W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.): 5811 GL

5. LEASE DESIGNATION AND SERIAL NO.: NM - 01614

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: Thompson

9. WELL NO.: 9

10. FIELD AND POOL, OR WILDCAT: Nenahezad - Dakota

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA: Sec. 28-31N-12W

12. COUNTY OR PARISH: San Juan

13. STATE: New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	☐	PULL OR ALTER CASING	☐
FRACTURE TREAT	☐	MULTIPLE COMPLETE	☐
SHOOT OR ACIDIZE	☐	ABANDON*	☐
REPAIR WELL	☐	CHANGE PLANS	☐
(Other)			

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	☐	REPAIRING WELL	☒
FRACTURE TREATMENT	☐	ALTERING CASING	☐
SHOOTING OR ACIDIZING	☐	ABANDONMENT*	☐
(Other)			☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-11-68 Rigged up workover unit. Pulled 1½" tubing.
7-14-68 Set 5½" Halliburton [illegible] at [illegible]. Squeezed Dakota w/100 sx cement [illegible].
7-17-68 Cleaned out to 7[illegible]
7-20-68 Perforated lower [illegible] Sand-water fraced lower Dakota with [illegible] 70, 70-5 - 2400# gel agent [illegible] A G 4000#.
7-21-68 Squeezed lower [illegible]
7-31-68 Drilled out cement to [illegible] gals USA acid, pulled tubing. Perforated Dakota [illegible] 7068-70, 7076-82. Fraced the Dakota with [illegible] sand, 20# WAC-11, 1% KCL, 10# CM-1, 60# [illegible] gal fluid.
8-1-68 Flow down to 7035
8-10-68 Set bridge plug [illegible] Nenahezad 5012-22, 4820-80, 2 SPF. Fraced with [illegible], used 45,700 gal water.
8-13-68 Ran tubing [illegible]; ran sliding sleeve [illegible].

Shut-in till in [illegible] on the 21st of August.

[illegible] Superintendent DATE 9-6-68
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
SEP 10 1968
OIL CON. COM.
DIST. 3

RECEIVED
SEP 10 1968
U. S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side