

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Wildcat	5. LEASE DESIGNATION AND SERIAL NO. 14-20-0603-5356
2. NAME OF OPERATOR Atlantic Richfield Company	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo
3. ADDRESS OF OPERATOR Box 2197, Farmington, New Mexico	7. UNIT AGREEMENT NAME Chevron Navajo
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 920' FWL & 510' FWL (Unit M) SW/4 SW/4 Sec. 19	8. WELL NO. 1
14. PERMIT NO.	10. FIELD AND POOL, OR WILDCAT Wildcat
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 5324' HLB 5356'	11. SEC. T., R., M., OR BLM. AND SURVEY OR AREA Sec. 19, T-22N, R-20W
	12. COUNTY OR PARISH San Juan
	13. STATE New Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
(Other) ☐	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On Feb. 3, 1967, set the following cement plugs through open ended drill pipe to plug and abandon.

From 5800 to 5550 with 65 ex. class "C" cement - 4 1/2 gal
4950 to 4850 with 35 ex. class "C" cement - 4 1/2 gal
3275 to 3175 with 35 ex. class "C" cement - 4 1/2 gal
1350 to 1241 with 30 ex. class "C" cement - 4 1/2 gal

Intervals between plugs filled with 9.5 lb/gal. mud. No cement plugs above 1241. This interval (1241' to surface) left accessible for possible use as water supply by Navajo Tribe as per instructions Mr. E. T. McGrath with the U.S.G.S. in Farmington.

Put 13 3/8" casing collar on top surface casing with plate welded on top of collar and with dry hole marker attached.

On 6/8/67 cleaned up location and filled pits.

To location: West of Shiprock toward Tee-See-Pee go 0.2 miles past Arizona State line sign and turn right. Go on main road 1.8 miles to Y and take left. Go 0.5 miles and take right. Go 0.4 mile up on small road to location. Location is 25 miles from Shiprock.

18. I hereby certify that the foregoing is true and correct

SIGNED

B. J. Bastian

TITLE

Orig. Prod. Supv.

DATE

6/16/67

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 20 1967

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-485229

507-0-51

