

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____
Lease No. 14-20-0603-7116

SUNDRY NOTICES AND REPORTS ON WELLS

| | | |
|---|--|----------|
| NOTICE OF INTENTION TO DRILL | SUBSEQUENT REPORT OF WATER SHUT-OFF | <u>X</u> |
| NOTICE OF INTENTION TO CHANGE PLANS | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF | SUBSEQUENT REPORT OF ALTERING CASING | |
| NOTICE OF INTENTION TO REDRILL OR REPAIR WELL | SUBSEQUENT REPORT OF REDRILLING OR REPAIR | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE | SUBSEQUENT REPORT OF ABANDONMENT | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING | SUPPLEMENTARY WELL HISTORY | <u>X</u> |
| NOTICE OF INTENTION TO ABANDON WELL | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

April 3, 1964

Navajo Tribal 21-36
Well No. 2 is located 1980 ft. from [N] line and 660 ft. from [E] line of sec. 36

31N 18W NMPM
(4th Sec. and Sec. No.) (Twp.) (Range) (Meridian)

San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5103 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Drilled 7-7/8" hole to total depth of 8127 feet. Ran logs. Cemented 4 1/2", 9.5 lb. per foot, J-55, ST&C new casing at 8121 feet with 450 sx. cement. W.O.C. 3:30 A.M., 3-22-64. W.O.C. 18 hours. Pressure tested 4 1/2" casing to 100 psi for 30 minutes, O.K. Nipped up tree. Perforated selected interval 7043-7093 with 8 shots. Now preparing to swab test.



Understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Texas, A Division of California Oil Company

Address Drawer "S"

Monahans, Texas

By S. J. Mathews, Jr.

Title District Superintendent