

(SUBMIT IN TRIPLICATE)

Indian Agency Shawnee

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Allottee _____

Lease No. 24-00-000-0000

Section 36

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WELL	SUBSEQUENT REPORT OF REDRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

November 3, 1965

Well No. 22-36-2 is located 2000 ft. from N line and 600 ft. from E line of sec. 36
22 or 22 1/2 Sec. 36 22 10 22
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Shawnee Shawnee Shawnee
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 2200 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mud jobs, cementing points, and all other important proposed work)

Casing Details: 13-5/8" 45 lb @ 80' Cemented to surface.
9-5/8" 35 lb @ 500' Cemented to surface.
4" 9.5 lb @ 500' Cemented with 400 ann.

Abandonment Operations

1. Seal casing with 10.3 lb/gal mud. Spot cement plug 700-800'.
2. Determine true point, shut off and pull removable 4" casing (not. 1000-3).
3. Spot cement plugs 300-350', 750-800', and surface - 25'.
4. Remove wellhead, with steel plate on 13-5/8" casing, clean up and level location and install abandoned well marker.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Standard Oil Company of Kansas - A Division of American Oil Company

Address 3000 Avenue B

Wichita, Kansas

By B. Davidson

Title Lead Drilling Engineer

RECEIVED

NOV 3 1965

U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

RECEIVED

NOV 4 1965

OIL CON. COM.