

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT - " for such proposals

5. Lease Designation and Serial No.

NMSF - 078097

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

HEATON LS

16

9. API Well No.

3004513134

10. Field and Pool, or Exploratory Area

Basin DAKOTA

11. County or Parish, State

San Juan

New Mexico

1. Type of Well

☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

AMOCO PRODUCTION COMPANY

Attention:

Nancy I. Whitaker

3. Address and Telephone No.

P.O. BOX 800 DENVER, COLORADO 80201

303-830-5039

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1843 FSL

1056 FWL

L

Sec. 28 T 31N R 11W

UNIT L

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other LETTER DTD 2-14-97

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

MIRUSU 11/14/96

TOH W/ 2 3/8" TBG. TIH W/CIBP, SET AT 6846. PRESSURE TEST CSG TO 500 PSI FOR 15 MIN. HELD OKAY. SPOTTED 72 SXS OF CLASS BE CEMENT ON TOP OF CIBP. EST. TOC AT 5022'.

SPOTTED ADDITIONAL 84 SXS CLASS B CEMENT FROM 3922 TO 5022'.

SPOTTED ADDITIONAL 130 SXS CLASS B CEMENT FROM 1950 TO 2664' PLUGGING THE 4 1/2 CSG.

SHOT SQUEEZE HOLES AT 1070' W/ 2JSPF .340 DIA. PUMPED 91 SXS CLASS B CEMENT. TIH AND TAGGED CEMENT AT 753'. SHOT SQZ HOLES AT 350' W.2 JSPF .340 DIA. PUMP 26 SXS OF CLASS B CEMENT DN CSG. CIRCULATED CEMENT TO SURFACE. CUT OFF WELL HED AND INSTALLED MARKER.

RDSUMO 11/20/96

RECEIVED
APR 11 1997

OIL CON. DIV.
DIST. 3

14. I hereby certify that the foregoing is true and correct

Signed

Nancy I. Whitaker

Title

Staff Assistant

Date

04-02-1997

(This space for Federal or State office use)

Approved by

Errol J. Beebe

Title

Patricia J. ...

Date

04-02-1997

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious, or fraudulent statements or representations as to any matter within its jurisdiction.

* See Instructions on Reverse Side

NMOC