Form C-122

MULTI-POINT BACK PRESSURE TEST FOR GAS WELLS Revised 12-1-55

ool	Basin			Fc	ormation_	Dake	ota		County_S	en Jua	n		
niti	al XX		Annua	1		Speci	al		Date of T	est1	<u>-27-6</u>	2	
ompa	ny Adobe	011 C	.		L	ease <u>St</u>	andard M	chols	Well	No	1		
nit	_ Se	c21	Twp	· <u>31</u>	nRge	• <u>13W</u>	Purch	aser	 				
Casing / 1/2 Wt. 10.5 I.D. Set at 6725 Perf. 6452 To 6600													
Tubing 2 3/8 Wt. 1.7 I.D. Set at 6586 Perf. Open ended To													
las F	ay: From_		To		L	xd	G_0_680_	GL	F	Bar.Pre	ss		
	cing Thru:												
rout	of Complet	lane s			Packer		Sing	le-Brade Reservo	nhead-G。(ir Temp	3. or G	.0. 1		
ate	of Complet	Lon:	<u>=7=62</u>		acker		ED DATA						
							ED DRIK		Two Tan	e			
'este	ed Through	Winds.		Choke)	Meden				Type Taps				
	Flow I (Choke)		low Da	lata				Data Temp.	Casing Data Press. Temp.		Duration		
10.	(Prover)	(Orif	ice)	rress		i .	•	1		or.	1	of Flow Hr.	
	Size			psig	h _w	°F•	psig	°F.	 	-F.	├	ur.	
SI							1939		1976	ļ	 		
2.													
3.	211	2H 3/4H		324		72			746_	 	3 hours		
5.			ļ		 								
No.	Coefficient (24-Hour) $\sqrt{h_{W}}$				Pressure	FLOW CALCULATIO Flow Temp. Factor Ft		Gravity	Facto	Compress. Factor Fpv		Rate of Flow Q-MCFPD @ 15.025 psia	
. 	(24-Hour) √ h _w p _f		Pi	F									
2. 3.	12-3650			336	0.9896		0.9393	1,0	1.036		4002		
4.		4.3070											
5.			L		PI	RESSURE	CALCULAT:	IONS					
Gas Liquid Hydrocarbon Ratiocf/bbl. Specific Gravity Separator Gas Gravity of Liquid Hydrocarbonsdeg. Specific Gravity Flowing Fluid F_C(1-e^{-S})P_C3952													
No.	P _w	P	2 t	F _c Q	(F _c Q)	2 ((F _c Q) ² (1-e ^{-s})	P _w 2	P _c -P _w		Cal.	P _w P _c	
1. 2.												1.1703	
3.	758	ļ						575	3377				
4. 5.													
	olute Poter	tial:	1.50	12		MCFP1	D; n <u>75</u>	1,12	52				
COM	PANYA	åaba_0	41 Co										
ADE	RESS 1	223 Po	trolo	m Idf	e Bldger	Mdla d	Temes						
WIT	NESSED	— 	- 24 - 1)	agen,						TEH	SAY.		
	IPANY					R	EMARKS		/ (atte	Aft	//	
									()	FFRS	196	2	

INSTRUCTIONS

This form is to be used for reporting multi-point back pressure tests on gas wells in the State, except those on which special orders are applicable. Three copies of this form and the back pressure curve shall be filed with the Commission at Box 871, Santa Fe.

The log log paper used for plotting the back pressure curve shall be of at least three inch cycles.

NOMENCLATURE

- Q I Actual rate of flow at end of flow period at W. H. working pressure (P_w). MCF/da. @ 15.025 psia and 600 F.
- Pc= 72 hour wellhead shut-in casing (or tubing) pressure whichever is greater.
- Pw Static wellhead working pressure as determined at the end of flow period. (Casing if flowing thru tubing, tubing if flowing thru casing.) psia
- Pt Flowing wellhead pressure (tubing if flowing through tubing, casing if flowing through casing.) psia
- Pf Meter pressure, psia.
- $h_{\mathbf{W}}$ Differential meter pressure, inches water.
- Fg Gravity correction factor.
- F_t Flowing temperature correction factor.
- F_{pv} Supercompressability factor.
- n I Slope of back pressure curve.

Note: If P_w cannot be taken because of manner of completion or condition of well, then P_w must be calculated by adding the pressure drop due to friction within the flow string to P_t .