31

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	Agency	
Pt MAS	· PANILLETTI	*1.7 DOT
	·	
Allotte	e	
	vo. 14-20-	

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF WATER SHUT-OFF
	SUBSEQUENT REPORT OF SHOOTING OR ACIDENCE LONG.
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO REDRILL OR REPAIR WEL	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	subsequent report of abandonment MAY 9 1960
NOTICE OF INTENTION TO PULL OR ALTER CASING	
NOTICE OF INTENTION TO ABANDON WELL	U. S. GEOLOGICAL SURVEY
	DURANGO, GOLO.
(INDICATE ABOVE BY CH	ECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
	5–6–60 , 19
Well No. 10 is located 660	ft. from $\binom{N}{g}$ line and 1310 ft. from $\binom{E}{w}$ line of sec. 31
IN ME Sec. 31 31N	14W 18579
(½ Sec. and Sec. No.) (Twp.)	
Vorde Gallup	San Juan Now Persion
(Field)	(County or Subdivision) (State or Territory)
The elevation of the derrick floor above	e sea level isft.
	DETAILS OF WORK
(Santa managed and a managed 1) and a to be a set of a mile	
(State names of and expected depths to objective sand ing point	s; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
	s, and all other important proposed work)
Spud 7:30 p.m. 5-4-60 drilling Can A jts. 125.49' of 8-5/80 0 142.50' K.B 13.80' from K.B. cement, 25 calcium chloride, c C.C. 24 borrs. Scot plug w/	11" hole to 145' D. 3rd 32# J-55 STOC CTOI cals. casing set to ground level. Cemented w/100 ex. regular iroulated to surface. Plug down 2:30 a.m. 5-5-60.
Spud 7:30 p.m. 5-4-60 drilling Can A jts. 125.49' of 8-5/80 0 142.50' K.B 13.80' from K.B. cement, 25 calcium chloride, c C.C. 24 borrs. Scot plug w/	11" hole to 145' D. 3rd 32# J-55 STOC CTOI cale. casing set to ground level. Cemented v/100 ex. regular iroulated to surface. Plug down 2:30 a.m. 5-5-60. 300 ped for 30 minutes, CV. MAY 1 1 1960 OIL CON. COM OIL CON. COM opproval in writing by the Geological Survey before operations may be commenced.
Spud 7:30 p.m. 5-4-60 drilling Can A jts. 125.49 of 8-5/80 0, 142.50 K.B 13.80 from K.B. cenent, 25 calcium chloride, cont. 24 bo re. Cost plug w/.	11" hole to 145' D. 3rd 32# J-55 STOC CTOI cale. casing set to ground level. Cemented v/100 ex. regular iroulated to surface. Plug down 2:30 a.m. 5-5-60. 300 ped for 30 minutes, CV. MAY 1 1 1960 OIL CON. COM OIL CON. COM opproval in writing by the Geological Survey before operations may be commenced.
Spud 7:30 p.m. 5-4-60 drilling Can A jts. 125.49 of 8-5/80 of 142.50 K.B 13.80 from K.B. concent, 2 calcium chloride, 2 calcium chloride, concent, 2 calcium c	11" hole to 145' D. 3rd 32# J-55 STOC CTOI cale. casing set to ground level. Cemented v/100 ex. regular iroulated to surface. Plug down 2:30 a.m. 5-5-60. 300 ped for 30 minutes, CV. MAY 1 1 1960 OIL CON. COM OIL CON. COM opproval in writing by the Geological Survey before operations may be commenced.