GRAND JUNCTION, CO

Integaion

- Illa Street,

Oil and Pas Co., a

UNITED STATES

GEOLOGICAL SURVEY

This into use the training for propose site of the chird deepen of plug back to a different reservoir luse form 3-331—0 for such proposess.

imision of Atlantic Richfield Company

4. LOCATION OF WELL (REPORT LOCATION DLEARLY, See space 1

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.

AT SUPFACE: 1980' FSL & 2080' FEL, Sed. 27

SUNDRY NOTICES AND REPORTS ON

P.O. Box 5540, Renver, Colo.

535

40

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

_{lelow.} Unit J,

AT TOTAL DEPTH:

AT TOP PROD. INTERVAL:

REPORT, OR OTHER DATA

PEQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (otner)

REPAIR WELL

DEPARTMENT OF THE INTERIOR N 1 2 1983

Sudget Bureau No. 42-71414

			4 -	· <u>-</u>	<u> </u>	20	4 –	- 3	<u> </u>
i.	IF IN	ZIAI	٧.,	AL:	_01	TEE	CR	TR	:8

5.	TE INCIAN.	ALLOT	TEE OR	TRIBE	NAM
		TT+ a	Vitn		

7.	UNIT AGREEMENT		
	Horseshoe	Gallup	Unit

			SE MAME	
Ξ	orse	since	Gallup	Unit

9. WELL NO

<u>15÷</u> 10. FIELD OR WILDOAT NAME

Horseshoe Gallup SEC., T., R., M., CRIBER, AND SURVEY DR

ABEA Sec. 27-31N-16W

12. COUNTY OR PARISH: 13. STATE

San Juan New Mexico

14, API NO

None Assigned 15. ELEVATIONS (SHOW DF, KDB, AND WD)

OIL CON. DIV.

5477' GR SUBSEQUENT REPORT OF NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates. including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 211-1-82

This notice supercedes our Sundry Notices dated August 31, 1982 on the subject well.

APCO now proposes to plug and abandon this well, as per the attached revised P & A Procedure.

(This is in compliance with the requirements as set forth in a memorandum dated September 30, 1981, and a subsequent letter of April 26, 1982 , both from the State of New Mexico, Energy and Minerals Department, Oil Conservation Division(copies attached to our August 31, 1982 Sundry Notice).

Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct SIGNED Steaker Kose TITLE Dist.Prod.Sup	December 30 November 1, 1982
APPROVED BY Original Signed - Scott L. Elis JOHN L. PROCE CONDITIONS OF APPROVAL IF ANY: District Supervisor	se)
Alignment of source and an arrange of the "See Instructions on Reverse Side	

HORSESHOE GALLUP UNIT INJECTION WELLS PLUGGING AND ABANDONMENT PROCEDURE (REV.SED)

- 1. MIRU.
- 2. Release packer and pull tubing and packer out of hole.
- 3. RIH with tbg open-ended to below the bottom perforation and pump sufficient cement to cover top perforation by 50' inside the casing.
- 4. POH w/tbg. GIH w/wireline and shoot enough holes in production string opposite 150' above top perforation to allow cement squeezing of zone. (This may be necessary since the original cement job may not have covered the Gallup formation by 50'). Squeeze sufficient cement to place a 100' plug outside the casing. Also, leave a 100' plug inside the casing. If unable to squeeze plug outside the casing, leave a 100' plug inside the casing.
- 5. POH w/tbg. GIH w/wireline and shoot enough holes in production casing opposite a point 50' below the surface casing shoe to allow squeezing cement.
- 6. RIH w/tbg open-ended and perform a braden-head squeeze of the perforations. Use sufficient cement for a 100' column behind the casing and a 100' plug inside the casing.
- 7. POH, cut casing one foot below ground level, place a 30' cement plug inside casing, weld on a blind flange, weld a dry hole marker on the blind flange, fill hole and move off.
- 8. Rehabilitate location and access road using stipulations supplied by the surface management agency.
- NOTE: BOP's will not be needed in most cases because expected reservoir pressure of the Gallup in the area of abandonment is very low. (Estimated at less than 250 300 psi bottom-hole.) If pressure does exist on any of the subject wells, bleed it off, install BOP's if needed, and commence with above procedure.

TABLE I

Horashoe Gallup Unit Federal Lease No. 14-08-001-8200 San Juan County, New Mexico.

list of Wells

		\$ €—;	_	
	: 10- -	-:-	÷	
3.	No.	103	Â	
4.	No.	105	4	
5.	No.	113	A	
/ 5.	∵::- :-	126	-Ĵ-	
7.	Nc.	130	C	
€.	Nc.	132	C	
9.	No.	135	C	
10.	No.	137	C	
11.	No.	139	Ç	
12.	No.	141	C	
13.	No.	143	D	
14.	No.	145	D	
15.	No.	148	D	
16.	No.	150	D	
17.	No.	152	D	
18.	No.	154	D	
19.	No.	156	D	
-20 -		-160		

21.	No.	215	2
	·ic.	162-	-6-
23.	No.	164	0
-24	No.	169	-) -
25.	No.	171	D
26.	No.	173	D
27.	No.	175	D
-28	NO.	-100-	
29.	No.	132	D
30.	Na.	184	9
31.	No.	186	٥
-32:-	No.	192	-D
33.	Nc.	194	D,
34.	No.	196	D
35	-No.	201	9
36.	No.	203	D
37.	No.	205	D
38.	No.	207	D
39.	No.	213	0
40.	No.	217	D

		No.	275 73	
			274	
	52.	No.	269	C
	51.	No.	263	C
	50.	No.	 261	C
	49.	No.	259	D
	48.	No.	250	0
· ./			248	
(State)	46.	No.	240	D
	45.	No.	238	D
		No.		D
(Stath)	43.	No.	227	5
	42.	No.	225	- y
	41.	No.	223	2