

DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

From 516' to 470'. The hole was filled with muds from 470' to 24'.

LOC OF CH OR CAS WITH

CONFIDENTIAL

There was no other person present in the room at the time.

Well No. 1 T314 R134 Meridian T. & P. Co. Copyright 1914

At which time a certificate was run to the bottom of the hole in

Cut for distribution. The well was left open until June 14, 1960.

The information given herewith is a complete and correct record of the well, and all work done on the well.

Ultraviolet lamp

THE ABOVE IS A SUMMARY OF THE INFORMATION RECEIVED FROM THE ABOVE SOURCES ON 10/10/60.

~~CONFIDENTIAL~~

The summary on this page is for the condition of the well at 8000 ft. During the drilling of this well, drilling was completed on 10/10/60.

Commenced drilling	June 8 1905	Finished drilling	June 8 1905

total depth of 720' oil or gas sands or zones

even, ALLIANCE was furnished with all the well was drilled to a

to from to from

set and cemented with 5 sacks of cement. After cement hard-

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

REKAB SITAHU TERASEBNI

THIS WELL WAS SPUN ON JUNE 6, 1960, AND DRILLED TO 20 FEET USING

to _____ from _____ of _____

..... of month, 4. of of month, 2. of

HISTORY OF OIL OR GAS WELL

Casing size	Per foot weight	Thickness of metal	Metal	Amount	Kind of steel	Cut and drilled from	From To—	Purpose
It is of the greatest importance to have a complete history of the well. Please state in detail the dates of re-drilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked," or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in, state kind of material used, position, and results of pumping or bailing.								

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

MUDLOGGING AND CEMENTING RECORD

Year	White	Number	of	Deaths	from	Heart	Disease
1900	102	1					

PLUGS AND ADAPTERS

Heaving plug—Material	Depth	Depth set
Adapters—Material	Size	

SHOOTING RECORD

[illegible]

TOOLS USED

Rosary tools were used from	0 feet to	750 feet, and from	feet to
Cable tools were used from	feet to	feet, and from	feet to

DATE

emulsion; and _____ % sediment.	_____ % water; and _____ % sediment.	_____ % water; and _____ % sediment.
The production for the first 24 hours was _____	The production for the first 24 hours was _____	The production for the first 24 hours was _____
_____ barrels of fluid of which _____ % was oil; _____	_____ barrels of fluid of which _____ % was oil; _____	_____ barrels of fluid of which _____ % was oil; _____
_____ Gravity, _____ °Bé.	_____ Gravity, _____ °Bé.	_____ Gravity, _____ °Bé.
_____ Part to producing _____	_____ Part to producing _____	_____ Part to producing _____

EMPLOYEES

[illegible]

FORMAT: RECORD

FROM-	TO-	TOTAL FEET	FORMATION
0	425	425	Black silty sandstone with occasional streaks of thin, blue, silty sandstone.
425	500	500	Black silty sandstone with occasional streaks of thin, blue, silty sandstone. (Continued from 425)
500	550	550	Black silty sandstone with occasional streaks of thin, blue, silty sandstone. (Continued from 500)