

9-331
1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

LL ☐ GAS ☒ WELL ☒ OTHER

NAME OF OPERATOR

1 Paso Natural Gas Company

ADDRESS OF OPERATOR

Box 990, Farmington, New Mexico - RM 87401

LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1150'N, 1050'E

5. LEASE DESIGNATION AND SERIAL NO.

RM 0607

6. INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Atlantic 6

9. WELL NO.

8

10. FIELD AND POOL OR WILDCAT

Antec Pictured Cliffs E

11. SEC. T. R. M. OF B.L. AND
SURVEY OR AREA

Sec. 8, T-21-N, R-10-W
N.M.P.M.

12. COUNTY OR PARISH 13. STATE

San Juan New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6056' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*


(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 8-28-67 spudded well, drilled surface hole and ran 6 joints 8 5/8", 2 1/2", J-55 casing (196.58') set at 208.08' w/170 sacks cement circulated to surface. W.O.C. 12 hours, tested w/600#/30 Min. O. K.

On 8-31-67 T. D. 2883', ran 91 joints 2 7/8", 6.4", J-55 casing (2873') set at 2883' w/240 sacks cement. W.O.C. until completion.

9-5-67 F.B.T.D. 2872'. Tested casing to 4000# O. K. Perf. Pictured Cliffs 2718-30', 2742-50' w/24 SPZ. Frac w/30,000# 10/20 sand, 34,860 gal. water. Max. pr. 4000#, BDP 1800#, tr. pr. 3000-3000-3600#. I.R. 25.9 BPM. Dropped 1 set of 25 balls, flushed w/672 gal. water. ISIP 500#, 30 Min. 400#.



18. I hereby certify that the foregoing is true and correct

Original Signed F. H. WOOD

SIGNED

TITLE Petroleum Engineer

DATE 9-7-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-582229

507-1851

