Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-01614
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas other	Thompson
Well Well Guide	9. WELL NO.
2. NAME OF OPERATOR	14 10. FIELD OR WILDCAT NAME
Southland Royalty Company 3. ADDRESS OF OPERATOR	Aztec Pictured Cliffs
P.O. Drawer 570, Farmington, New Mexico	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.)	Section 28, T31N, R12W
AT SURFACE: 1650' FSL & 1080' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT. OR OTHER DATA	15 ELEVATIONS (CHOW DE KED AND WE)
	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6270' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF RECEIV	/FID
FRACTURE TREAT SHOOT OR ACIDIZE	(hacker)
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING U	charge on Form 9–330.)
MULTIPLE COMPLETE CHANGE ZONES U. S. CEULUAIGA	LSURVEY
ABANDON*	N. 15.
(other) X Request for Temporarily Abandonment	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, give subsurface locations and
SOUTHLAND ROYALTY COMPANY proposes to tempora gas well. A cement retainer will be set at 2 perforations (2624'-38') will be squeezed wit Well will remain in this status until further potential is completed.	1590' and the Pictured Cliffs The 20 sacks of Class "B" cement. The evaluation of Fruitland
Temporary abandonment is approved for one year. Rehabilitate all disturbed surface except that	
necessary to service the wel	(,
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED K. Fielde Dist. Enginee	pate February 16,1982
APPROVED ace for Federal or State of	
APPROVED BY TOTAL TITLE	DATE
conditions of Approval EBN19 1982	

MMOCC

Instructions on Reverse Side

FOWJAMES F. SIMS DISTRICT ENGINEER